

			X

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079456
Unit H11

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Sandfrac Treatment</u> X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 27th, 1957

Well No. 1 is located 390 ft. from N line and 390 ft. from E line of sec. 20

NE/4 NE/4 Sec. 20
(1/4 Sec. and Sec. No.)

24N
(Twp.)

31
(Range)

N.M.P.M.
(Meridian)

S. Blanco PC Ext.
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6973 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate sanding jobs, cementing points, and all other important proposed work)

11-4-57 TD 3145'. Cleaned out to 3111'. Perforated 3066-74' and 3096-3108' with 4 shots per foot. Sandfraced with 25,000 gallons water and 30,000# sand, flushed with 3,000 gallons water. Breakdown pressure 1650#. Treating pressure 1500#. Dropped 40 rubber balls. Treating pressure increased to 2300#, broke to 2000#. Average injection rate 54.2 barrels per minute.

11-5-57 After 11-hour blow flowing 699 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTIN-GREEN DRILLING CORP.

Address 405 1/2 West Broadway

Farmington, New Mexico

By _____

Title Vice-President