

(SUBMIT IN TRIPLICATE)

Indian Agency Dulce, New Mexico

UNITED STATES

Jicarilla ApacheDEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYAllottee Cont. #11-Trust #19Lease No. J. Apache #2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report for setting 3 1/2"</u>	
	<u>Casing</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 2, 1963Well No. 11 is located 1000 ft. from [N] line and 1000 ft. from [E] line of sec. 19SW/NE/SE-Sec-19
(1/4 Sec. and Sec. No.)24N
(Twp.)5W
(Range)MMPM
(Meridian)Basin Dakota
(Field)Rio Arriba
(County or Subdivision)New Mexico
(State or Territory)The elevation of the derrick floor above sea level is 6508' ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs; cementing points, and all other important proposed work.)

2-28-63 - 6665' Total Depth:

Set 3 1/2" OD 9.2#, SRT, J55, Non-UP SS Casing At 6641' w/Howco Shoe on bottom and Howco Float Collar @ 6608', w/Scratchers & Centralizers from (6608'-6600') With D.V. Staging tool in string at 2235'.

Cemented by Halliburton, First stage in Dakota Zone w/250 Sacks 50/50 Formix cement, w/12 1/2# Gilsenite per Sack, mixed 4% Gel, & 3/4% CPR2, and 100 Sacks 50/50 Formix Cnt. No gel, & 3/4% CPR2, Max. Press. 2000#, Pumped plug to 6607' w/2500# Press. at 4:00 PM, Csg. Hydro-Tested w/4000# Press.

WOC - And ran Temp. (BAR) Survey, top of cement outside 3 1/2" Csg. lower stage at 5250'.

Cemented second stage by Halliburton through D. V. Staging tool at 2235' with 75 Sacks Class "C" Cnt. mix 6% Gel, (To cover P-C Formation) Pump plug to 2235' Ran Temp. Survey, top of Cnt. at 1470' above P.C. Formation. WOC.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum CorporationAddress Box 1469, Durango, ColoradoPH-247-5353By D.F. Furse D.F. FurseTitle Production Foreman