rm 3160-5 me 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

6. If Indian, Allottee or Tribe Name

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

JICARILLA

TRIBAL #69

	<del></del>		
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation		
ype of Well Oil X Gas Well X Well Other	8. Weil Name and No.		
ame of Operator	APACHE FEDERAL #12		
FLOYD OIL COMPANY	9. API Well No.		
address and Telephone No.	30-039-05468		
711 LOUISIANA, SUITE 1740, HOUSTON, TEXAS 77002	10. Field and Pool, or Exploratory Area		
ocation of Well (Footage, Sec., T., R., M., or Survey Description)	BALLARD PICTURED CLIFFS		
1650' FSL & 1650' FEL of Sec. 17T, 24N, R5W	11. County or Parish, State		
RIO ARRIBA COUNTY, NM.	RIO ARRIBA, NM		
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA		

TYPE OF SUBMISSION		TYPE OF ACTION	
X Notice of Intent DE	Abendonment		Change of Plans
	Recompletion	· :	New Construction
Subsequent Report	3 U 1300 L Plugging Back		Non-Routine Fracturing
	Casing Repair		Water Shut-Off
Final Abandonment Notice	Altering Casing	닐	Conversion to Injection
	Other		Dispose Water
<u> </u>	Allendo Co		e: Report results of multiple completion on Well spletion or Recompletion Report and Log form.)

i. Describe Proposed or Completed Operations (Clearly state all pertment details, and give pertment dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PLUG BY SPOTTING THE FOLLOWING PLUGS;

- 1) 100' of Class 'B' + 6% gel plug 2181'-2282' across Pictured Cliff Formation.
- 2) Perforate 50' below surface casing set @ 228'. Pump Class 'B' + 6% gel down 2 3/8 and circulate to surface.
- 3) Cut casing off 3' below ground level and install regulation dry hole marker.

NOTE: A 40 SEC/QT VISCOSITY, 8.34 #/gal MUD WILL BE USED TO SPOT ALL PLUGS.

0-1			
I hereby certify that the foregoing is true and correct Signed	Tide MANAGER OF PRODUCTION	Date	3/10/95
(This space for Foderal or State office use)  Approved by Robert Conditions of approval, if any:	Title Chief, Lands and Mineral Resources	Date _	MAR 2 9 1995

ide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements r representations as to any matter within its jurisdiction.