

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-03595

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

BCO, Inc.

3. ADDRESS OF OPERATOR

P. O. Box 669 Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1850 FNL 990 FEL 18-24N-7W NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GL 7270

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Escrito Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

18-24N-7W NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data (Eliz #1)

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

Plug Gallup

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Squeeze existing perforations (5920 - 6020) in Skelly Zone with 75 sacks of cement. 5 1/2" bridge plug will then be cemented in place which is covering perforations from 6108 -33. Let cement stabilize, tag bottom to see where plug is.

Run cement bond and compensated neutron logs over Point Look Out. If cement behind pipe perforate 4980' -4995. If no cement block squeeze may be considered by operator.

NOTE:

Verbal approval from USGS-Durango and OCC Aztec obtained 5-28-74.



18. I hereby certify that the foregoing is true and correct

SIGNED

Harry B. Bugh

TITLE President

DATE

5-28-74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

