

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-03010

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

John S. Dashko "B"

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

SW/4 SE/4 Section 11

T-24-N, R-7-W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

1.

OIL  
WELL ☐ GAS  
WELL ☒ OTHER

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

P. O. Box 480, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1190 FSL and 1800 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

RD 6969'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

As a result of no commercial shows of oil or gas, we propose to plug and abandon the John S. Dashko "B" No. 3 as follows:

1. Spot 80 sacks cement from TD 7000' to 6800' (Top of Main Dakota 6930', Graneros sandy shale 6864', Graneros shale 6737', and Greenhorn shale 6667').
2. Spot 60 sacks cement 6050' to 5800' (Top of Lower Gallup 5973').
3. Spot 40 sacks cement 5780' to 5600' (Top of Gallup 5733').
4. Spot 40 sacks cement 4000' to 3900' (Top of Mancos 4005' and Mesaverde 3975').
5. Spot 50 sacks cement 2450' to 2350' (Top of Lewis shale 2511' and Pictured Cliffs 2420').
6. Spot 40 sacks cement 400' to 300' (2-5/8" surface casing set at 372').
7. Spot 5 sacks 15' to surface.

Will erect abandonment marker and clean up location at later date.

Verbally approved 8-27-65 Ward to Hollingsworth.

18. I hereby certify that the foregoing is true and correct

SIGNED G. W. Eaton, Jr.TITLE Area EngineerDATE August 30, 1965

(This space for Federal or State office use)

APPROVED BY [Signature]  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

RECEIVED

SEP 2 1965

ON. COM.  
DIST. 3

RECEIVED

SEP 1 1965

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

