## UNITED STATES DEPARTMENT OF THE INTERIOR CONTROL OF T

		L OLIM	approvi	ea.		
		Budge	t Bures	ui No	. 42-	23119
-2-						
Э.	LEASE	DESIG	NATION	AND A	SERIA	1. 50.

GEOLOGICAL SURVEY	NM-03010			
SUNDRY NOTICES AND REPORTS  (Do not use this form for proposals to drill or to deppen of place the "APPLICATION FOR PERMIT -" for such	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
on GAS OTHER Dry Hole	7. UNIT AGREEMENT NAME			
2. NAME OF OPERATOR	8. FARM OR LEASE NAME			
Pan American Petroleum Corporation 3. ADDRESS OF GPERATOR				
Security Life Building, Denver, Co	olorado			
4. LOCATION OF WELL (Report location clearly and in accordance with an See also space 17 below.) At surface	y State requirements.* 10. FIELD AND POOL, OR WILDCAT			
1190FSL and 1800 FEL	Basin, Dakota  11. sec., T., R., M., OR BLK, AND			
	SW/4 SEA4 Section 11			
14. PERMIT NO. 15 RIFUATIONS (Shaw whether a	T-24-N, R-7-W			
14. PERMIT NO. 15. ELEVATIONS (Show whether p				
	Rio Arriba   New Mexico	١		
Notice of intention to:	Nature of Notice, Report, or Other Data			
	SUBSEQUENT REPORT OF:			
FRACTURE TREAT PULL OR AUTER CASING MULTIPLE COMPLETE	WATER SHUT-OFF REPAIRING WELL			
SHOOT OR ACIDIZE ABANDON*	FRACTURE TREATMENT  SHOOTING OR ACCIDIZING  ABANDONMENT*  X			
REPAIR WELL CHANGE PLANS	(Other)			
(Other)	Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
proposed work. If well is directionally drilled, give subsurface location to this work.)*	of details, and give pertinent dates, including estimated date of starting any ations and measured and true vertical depths for all markers and zones perti-			
well on 8-28-65 as follows:  1. Spotted 80 sack cement plug from TD 7000 Shale 6864, Graneros Shale 6737, Greenho	0' to 6800'(Top Main Dakota 6930', Graneros Sandy orn Shale 960/').			
2. Spotted 60 sack cement plug from 6050'	to 5900' (Top of Lower Gallup 5973')			
3. Spotted 40 sack cement plug from 5780'				
	to 3900'(Top of Mancos 4905, Mesa Verde 3976')			
	o 2350 (Top of Lewis Shale 2511, Pictured Cliffs24	20		
6. Spotted 40 sack cement plug from 400' to	o 300' (S 5/8" Surfaced Casing set at 372')			
7. Spotted 5 sack cement plug from 15' to	Surface. RULIVED			
8. Hole filled with heavy fluid between plu	SEP 23 1965			
9. Erected abandonment marker and cleaned a				
8. I hereby certify that the foregoing is true and correct SIGNED R.H. Beers TITLE Adn	ministrative Assistant DATE 9/16/54			
(This space for Federal or State office use)	RECEIVED			
APPROVED BYTITLE				
CONDITIONS OF APPROVAL, IF ANY:	SEP 22 1965			

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY FARMINGTON, N. M.

	4