## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5.	LEASE	
SF	078877	

6.	IF INDIAN,	ALLOTTEE OR	TRIBE NAME

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	Canyon Largo Unit
	8. FARM OF LEASE NAME
1. cii gas weil other	Canyon Largo Unit 9. WELL NO.
2. NAME OF OPERATOR	118
Merrion Oil & Gas Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Devils Fork Gallup
P. O. BOx 1017, Farmington, New Mexico 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17	AREA
below.)	Sec. 8, T24N, R6W
AT SURFACE: 1090' FSL and 800' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH:	Rio Arriba New Mexico
Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
RECUEST FOR APPROVAL TO: SUBSECUENT PERCET OF	6570'GL .
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: ' TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE REPAIR WELL	
REPAIR WELL	(NOTE: tepper results of multiple completion or zone
PULL OR ALTER CASING AMULTIPLE COMPLETE	describe on Folk 9-530.
MULTIPLE COMPLETE JUL 0 6	1984
(other) OIL CON	BUREAU OD MANAGEMEN FARMINGTON RESOURCE AREA
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subsurface locations and
Placed 25 sx (30 cu. ft.) Class B across Gallup	
Placed 25 sx (30 cu. ft.) Class B across Mesave	
Shot squeeze holes @ 3690'.	
Placed 25 sx inside and outside casing, 3690 -	3590'. (30 cu. ft. Class B)
Placed 25 sx (30 cu. ft.) Class B from 2250 - 1	
Fruitland.	
Placed 25 sx (30 cu. ft.) Class B from 1700 - 1	370' to cover Ojo Alamo.
Places 30 sx (35 cu. ft.) Class B from 370 - su	rface.
Pumped 35 sx (41 cu. ft.) Class B down Bradenhe	ad
Pumped 10 sx (11.8 cu. ft.) Class B surface plus	g.
Erected dry hole marker.	
Sucsumace Safety Valve: Manu. and Type	Set @ Ft.
15. Thereby contify that the foregoing is true and correct	
S GVED THE Operations Man	nagemate 6/28/84
(This space for Regeral or State office	ce use)
·	
APPROVED BY	DATE