



(SUBMIT IN TRIPLICATE)

 UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

 Land Office Santa Fe  
 Lease No. SP 079086  
 Unit Mexico-Ped "A"

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	1959
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Report of 1st & 2nd Perforations	X
	Report of Sand/Oil Free Jobs 1/14/59	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 18, 1959

 Mexico-Ped "A"  
 Well No. 1 is located 1450 ft. from [S] line and 990 ft. from [E] line of sec. 10

SE/4 Section 10

(4 Sec. and Sec. No.)

 Indesignated - Gallup  
 Indesignated - Indian

 24N  
 (Twp.)

 6W  
 (Range)

 N.M.P.M.  
 (Meridian)

 Rio Arriba  
 (County or Subdivision)

 New Mexico  
 (State or Territory)
The elevation of the derrick floor above sea level is 6475 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated 7" casing w/4 Lane Wells bullets per ft. as follows: 6675-79' (21'), 84 holes.

 Fraced Dakota formation down 2 1/2" tubing w/15,000# 40/60 sand & 25,000 gals. crude oil by  
 Dowell. 1/20# of Adomite added to each gal. oil. RSP 3450#, broke to 3000#. Max. TP 5050#,  
 Min. TP 3850#, Inj. rate 8 BPM. Flashed w/69 bbls. crude oil. 5 shut-down pressure 3000#.  
 Standing pressure in 10 min. 2900#.

 Perforated 7" casing w/4 Lane Wells bullets per ft. as follows: 6585-88', 6579-6605' & 6612-  
 16', total 13', 52 holes.

 Fraced Dakota formation, down 2 1/2" tubing thru 7" casing perfor. 6585-88', 6579-6605' & 6612-16'  
 w/10,000# 40/60 sand & 20,160 gals. crude oil by Dowell. Added 400# Adomite to free oil.  
 RSP 5400#, Max. TP 5400#, Min. TP 4600#, flushed w/80 bbls. oil. Inj. rate 8.5 BPM. Shut-down  
 pressure 3100#, and that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.
Company BYTNEY OIL COMPANY

Box 413

Address Washington, New MexicoBy (Signed) P. E. GosperTitle District Superintendent



Group	Condition 1	Condition 2	Condition 3	Condition 4
Control	65	75	80	85
Low	65	80	75	60
High	65	85	75	65
Very High	65	90	75	65

the 1990s, the number of people in the world who are under 15 years of age is expected to increase from 1.1 billion to 1.5 billion. The number of people aged 65 and over is expected to increase from 200 million to 400 million. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion. The number of people aged 15 and over is expected to increase from 3.5 billion to 4.5 billion.