W. LONG

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Indian Agency
Jicarilla
Allottee Contract #126
Lease No.

NOTICE OF INTENTION TO DRILL	SUBSEQUEN	IT REPORT OF WATER SHUT-OFF	X_
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUEN	IT REPORT OF SHOOTING OR ACIDIZ	ING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUEN	IT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUE	IT REPORT OF REDRILLING OR REPA	IR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUEN	IT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMEN	ITARY WELL HISTORY.	<u>, , , , , , , , , , , , , , , , , , , </u>
NOTICE OF INTENTION TO ABANDON WELL			
			•
(INDICATE ABOVE BY CHECK MA	ark nature of Repo	RT, NOTICE, OR OTHER DATA)	egiche A
	*************	September 6	, 19 <u>.56</u>
Vell No. "S" 11-11 is located 1090 ft. E/4 NE/4 11 24N (M Sec. and Sec. No.) (Twp.)	()	nd 1090 ft. from in lin	e of sec11
	o Arriba	New Mexico	<u> </u>
lideat Pictured Cillis	inty or Subdivision)	(State or Ten	ritory)
DET	TAILS OF WO	RK	mudding jobs, cemez
DET	TAILS OF WO	RK engths of proposed casings; indicate a proposed work)	0#8-RD
Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	RK engths of proposed casings; indicate is proposed work) .79' of 7'' OD J-55 20 dide shoe @ 3233.21'.	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float of	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	RK engths of proposed casings; indicate is proposed work) .79' of 7'' OD J-55 20 dide shoe @ 3233.21'.	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	RK engths of proposed casings; indicate is proposed work) .79' of 7'' OD J-55 20 dide shoe @ 3233.21'.	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	RK engths of proposed casings; indicate is proposed work) .79' of 7'' OD J-55 20 dide shoe @ 3233.21'.	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	RK engths of proposed casings; indicate is proposed work) .79' of 7'' OD J-55 20 1 ide shoe @ 3233.21'. OO am 8-22-56. After	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	engths of proposed casings; indicate proposed work) 79' of 7" OD J-55 20 10 am 8-22-56. After	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:	engths of proposed casings; indicate proposed work) 79' of 7" OD J-55 20 10 am 8-22-56. After	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float o with 150 sx 8% gel & 50 sx nea	rails of Wo waizes, weights, and is all other important; and set 3219 collar and grate. POB 11:6 ing ahead.	engths of proposed casings; indicate is proposed work) 79' of 7" OD J-55 20 aide shoe @ 3233.21'. 00 am 8-22-56. After OIL CON. COM.	0#8-RD Cemented
DET tate names of and expected depths to objective sands; show ing points, and a poin	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grat. POB 11:00 ing ahead.	engths of proposed casings; indicate is proposed work) 79' of 7" OD J-55 20 aide shoe @ 3233.21'. 00 am 8-22-56. After OIL CON. COM.	0#8-RD Cemented 30 hrs
DET tate names of and expected depths to objective sands; show ing points, and a point of the sands of the s	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grat. POB 11:00 ing ahead.	engths of proposed casings; indicate is proposed work) 79' of 7" OD J-55 20 aide shoe @ 3233.21'. 00 am 8-22-56. After OIL CON. COM.	0#8-RD Cemented 30 hrs
DET tate names of and expected depths to objective sands; show ing points, and so ing po	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grat. POB 11:00 ing ahead.	engths of proposed casings; indicate is proposed work) 79' of 7" OD J-55 20 aide shoe @ 3233.21'. 00 am 8-22-56. After OIL CON. COM.	0#8-RD Cemented 30 hrs
DET tate names of and expected depths to objective sands; show ing points, and a poin	TAILS OF WO waizes, weights, and is all other important; and set 3219 collar and grat. POB 11:00 ing ahead.	engths of proposed casings; indicate is proposed work) 79' of 7" OD J-55 20 aide shoe @ 3233.21'. 00 am 8-22-56. After OIL CON. COM.	0#8-RD Cemented 30 hrs
DET tate names of and expected depths to objective sands; show ing points, and so Drilled 8-3/4" hole to 3233' a CF&I casing with Baker float of with 150 sx 8% gel & 50 sx nea WOC, casing tested OK. Drilli I understand that this plan of work must receive approva-	rails of wo	engths of proposed casings; indicate is proposed work) 79' of 7" OD J-55 20 aide shoe @ 3233.21'. 00 am 8-22-56. After OIL CON. COM.	0#8-RD Cemented 30 hrs