

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well

GAS

RECEIVED
OCT 27 1995

2. Name of Operator

MERIDIAN OIL

OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FNL, 990' FEL, Sec. 11, T-24-N, R-3-W, NMPM

5. Lease Number

SF-078912

6. If Indian, All. or Tribe Name

7. Unit Agreement Name

Lindrith Unit

8. Well Name & Number

Lindrith Unit #24

9. API Well No.

30-039-05597

10. Field and Pool

Basin Fruitland Coal/
~~So Blanco Piet. Cliffs~~

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

9-20-95 MIRU. ND WH. NU BOP. TOO H w/102 jts 2 3/8" tbg. TIH w/5 1/2" cmt retainer, set @ 3077'. PT tbg to 1500 psi, OK. Establish injection. Plug #1: pump 40 sx Class "B" cmt below cmt retainer, 28 sx Class "B" cmt above cmt retainer to 2830'. TOO H to 2030'. PT csg to 500 psi/5 min, OK. TOO H. RU, perf 4 sqz holes @ 2086'. RD. Load hole. Establish injection. TIH w/5 1/2" cmt retainer, set @ 2030'. Establish injection. Plug #2: pump 36 sx Class "B" cmt below cmt retainer outside csg @ 1986-2086', 11 sx Class "B" cmt above cmt retainer, TOC @ 1933'. POOH. TIH, perf 2 sqz holes @ 149'. TOO H. Establish circ out bradenhead w/9 bbl wtr. Plug #3: pump 59 sx Class "B" cmt @ 149' to surface. Circ 1 bbl cmt to surface. SDON.

9-21-95 ND BOP. Cut off WH. Fill 8 5/8" csg w/3 sx Class "B" cmt. Install dry hole marker w/12 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 9-21-95.

14. I hereby certify that the foregoing is true and correct.

Signed *Debra Bradfield* Title Regulatory Administrator Date 9/22/95

(This space for Federal or State Office use)

APPROVED BY *Robert Kent* Title Chief Lands and Mineral Resources Date OCT 25 1995

CONDITION OF APPROVAL, if any: