



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau 42-R358.3.  
Approval expires 12-31-55.

Land Office Santa Fe  
Lease No. N.M. 09011  
Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 5, 19 55

Well No. 1 is located 990 ft. from S line and 990 ft. from E line of sec.

SW-4 of SE-4 Sec. 6  
(1/4 Sec. and Sec. No.)

24N 3 E.  
(Twp.) (Range)

N.M.P.M.  
(Meridian)

Wildcat  
(Field)

Rio Arriba  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6101.2 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TO DRILL WITH ROTARY TOOLS:

Set 150' 9-5/8" x 32.20 # casing and cement with 100 skn regular cement.  
Drill approximately 3200' to test pictured cliffs formation - set approx  
3200' 5-1/2" x 15.50# casing and cement with 100 skn regular cement.  
Drill plug and complete by frac with 13,000 gallons #2 diesel oil, and  
proper blend of sand.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company J. Felix Hickman  
Address 4115 Avenida La Rosolana NE  
Albuquerque, New Mexico

By J. Felix Hickman  
Title Operator

