(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Indian Agency
Jicarilla
Contract #126
Allottee
Lease No

	TION TO DRILL		SUBSEQU	JENT REPORT OF	WATER SHUT-OFF		X	
NOTICE OF INTEN	TION TO CHANGE PLANS.		SUBSEQU	JENT REPORT OF	SHOOTING OR AC	IDIZING	 -	
NOTICE OF INTEN	TION TO TEST WATER SH	IUT-OFF	SUBSEQU	JENT REPORT OF	ALTERING CASING	3-M-E	@- 	ve
NOTICE OF INTEN	TION TO REDRILL OR RE	PAIR WELL	SUBSEQU	JENT REPORT OF	REDRILLING OR	REPAIR 5	<u> </u>	VL
	TION TO SHOOT OR ACID			JENT REPORT OF		<u>n</u> n		1000
	TION TO PULL OR ALTER		SUPPLEN	MENTARY WELL HI	STORY	t	AN 12	1960
NOTICE OF INTEN	ITION TO ABANDON WELL							
	(INDICATE ABO	OVE BY CHECK MA	ARK NATURE OF RE	Port, notice, or		FARMIN	EOLOGICA NGTON, NE	W MEXIC
			**********		Janua	ry 11	, 19 .6	9
Jica Well No. 2.	arilla 1 is located	1 790 ft.	from N line	and 1555	ft. from W	line of sec	c. 1	
NR NV	1	24X	47	100				
(¼ Sec. and		(Twp.)	(Range)	(Me	ridian)			
South Blas		Blo Arr	unty or Subdivision)		(State o	r Territory)		
	of the	d						
State names of and	d expected depths to obje		TAILS OF W w sizes, weights, an all other importan		osed casings; indi	cate mudding j	jobs, cemen	t
Drld 7-7/1 jts of 2-1 set at 330 sx reg.	8" hole to 300 7/8" QB J-55 6	orive sands; shoring points, and O'. Drld .5# 8 RD centralise with ful	waizes, weights, an all other important leading the same and the same are a 20° real at leading the 20° real at leading the same are a 20° real at leading t	le fr 3000 with Bake ote scrate ion. PGB	to TD 3 or float si hers. Ce 4:30 A.M.	320'. Re hoe, T.Z. nented wi 1-10-60,	n 109 . 3295' ith 109	
Drld 7-7/1 jts of 2-1 set at 330 sx reg.	B" hole to 300 7/8" QD J-55 6 06'. Used 3 c Rotated casing	orive sands; shoring points, and O'. Drld .5# 8 RD centralise with ful	waizes, weights, an all other important leading the same and the same are a 20° real at leading the 20° real at leading the same are a 20° real at leading t	le fr 3000 with Bake ote scrate ion. PGB	to TD 3 or float si hers. Ce 4:30 A.M.	S20'. Rehoe, T.R. mented with 1-10-60.	an 109 . 3395' ith 100 . After	
Drld 7-7/1 jts of 2-1 set at 330 sx reg. 1 30 hrs WO	B" hole to 300 7/8" OB J-55 6 06'. Used 3 c Rotated casing C tested casin	otive sands; shoring points, and O'. Drld .5# 8 MD centralize with full g with 15	waizes, weights, an all other important leading the searing are a 20° to 1 circulat.	le fr 3000 with Bake ote scratc ion. PCB	to TD 3: or float si hers. Ce 4:30 A.M. rep to pe	S20'. Roboto T.X. nented with 1-10-60.	an 109 . 3395' ith 100 . After	
Drld 7-7/1 jts of 2-1 set at 330 sx reg. 1 30 hrs WO	B" hole to 300 7/8" QD J-55 6 06'. Used 3 c Rotated casing	otive sands; shoring points, and O'. Drld .5# 8 RD centralize with ful g with 15	waizes, weights, an all other important leading the searing are a 20° to 1 circulat.	le fr 3000 with Bake ote scratc ion. PCB	to TD 3: or float si hers. Ce 4:30 A.M. rep to pe	S20'. Roboto T.X. nented with 1-10-60.	an 109 . 3395' ith 100 . After	
Drld 7-7/1 jts of 2-1 set at 330 sx reg. 1 30 hrs wo	B" hole to 300 7/8" OB J-55 6 06'. Used 3 c Retated casing C tested casin	octive sands; showing points, and O'. Drld .5# 8 MD centralize with full g with 15	waizes, weights, an all other important leading the searing are a 20° to 1 circulat.	le fr 3000 with Bake ote scratc ion. PCB	to TD 3: or float si hers. Ce 4:30 A.M. rep to pe	SZO'. Rahoo, T.Z. hoo, T.Z. nented with the state of the	an 109 . 3395' ith 100 . After	
Drld 7-7/1 jts of 2-1 set at 33 sx reg. 1 30 hrs WO	B" hole to 300 7/8" QB J-55 6 06'. Used 3 c Retated casing C tested casin at this plan of work must Johnston-She 3010 Nonte V	octive sands; showing points, and O'. Drld .5# 8 RD entralize with full g with 15 at receive approve Asta RR	waizes, weights, an all other important leading the searing are a 20° to 1 circulat.	d lengths of proposit proposed work) le fr 3000 with Bake ote scrate ion. PCB s. CK. P	to TD 3: or float si hers. Ce 4:30 A.M. rep to pe	SZO'. Rahoo, T.Z. hoo, T.Z. nented with the state of the	an 109 . 3395' ith 100 . After	
Drld 7-7/1 jts of 2-1 set at 330 sx reg. 1 30 hrs wo	B" hole to 300 7/8" OB J-55 6 06'. Used 3 c Rotated casing C tested casin	octive sands; showing points, and O'. Drld .5# 8 RD entralize with full g with 15 at receive approve Asta RR	waizes, weights, an all other important leading the searing are a 20° to 1 circulat.	le fr 3000 with Bake ote scratc ion. PCB	to TD 3: or float si hers. Ce 4:30 A.M. rep to pe	SZO'. Rahoo, T.Z. hoo, T.Z. nented with the state of the	an 109 . 3395' ith 100 . After	

Control of the State of the Control of the Control