

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

Sundry Notices and Reports on Wells OCT 28 PM 3:41

1. Type of Well  
GAS

2. Name of Operator  
**MERIDIAN OIL**

3. Address & Phone No. of Operator  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M  
1190'FNL, 1500'FEL, Sec.4, T-24-N, R-6-W, NMPM

5. Lease Number  
SF-078874

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

Canyon Largo Unit

8. Well Name & Number  
Canyon Largo U #64

9. API Well No.  
30-039-05670

10. Field and Pool  
Basin Fruitland Coal

11. County and State  
Rio Arriba Co, NM

RECEIVED  
NOV - 3 1994  
OIL CON. DIV.  
DIST. 3

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

## 13. Describe Proposed or Completed Operations

10-21-94 MIRU. ND WH. NU BOP. POOH w/67 jts 2 3/8" tbgs. TIH w/cmt retainer, set @ 1908'. SDON.

10-22-94 Sting out of cmt retainer & load well w/2 bbl wtr. PT csg to 500 psi. Sting into cmt retainer. Plug #1: pumped 52 sx cmg below retainer, pressured up to 500 psi. Spot 9 sx cmt above cmt retainer. TOOH. POOH to 1655'. Reverse circ well clean w/13 bbl wtr. Perf 2 sqz holes @ 1648'. Set cmt retainer @ 1595'. Plug #2: pumped 63 sx cmt below retainer @ 1455-1648', sqzd off @ 1000 psi. Spot 16 sx cmt above cmt retainer to 1450'. TOOH. Perf 2 holes @ 184'. Establish circ down 5 1/2" csg and out bradenhead w/5 bbl wtr. Plug #3: pump 63 sx Class "B" cmt @ 184' to surface. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Install P&A marker w/15 sx cmt. RD. Rig released. Well plugged & abandoned 10-22-94.

## 14. I hereby certify that the foregoing is true and correct.

Signed *[Signature]* Title Regulatory Affairs Date 10/25/94

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

APPROVED

OCT 31 1994

DISTRICT MANAGER