

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3360, Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 543' FNL & 1912' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Plug Back ☒

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

Contract #68

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Jicarilla "B"

9. WELL NO.

16

10. FIELD OR WILDCAT NAME

Otero Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 6 - T24N - R5W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

14. API NO.

--

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6771' DF, 6762' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Plug Gallup zone which has been shut-in since February, 1978 (perforations are from 5956' to 6056').

On 10/14/80, TIH w/ Newsco's 1" endless coil tbg. inside of 2 3/8" tbg. Tool stopped @ 5427'. Cut off 2 3/8" tbg. w/ chemical cutter @ 5401' in center of jt. Pull up to 5400'. HOWCO cemented w/ 35 sx. Class "B" cement down 2 3/8" tbg. Displace to 5400'. POH 172 jts of 2 3/8" tbg. Dresser perfed 1' @ 4230' w/ 4 holes. TIH w/ 5 1/2" ESZV cement retainer. Set @ 4130'. TIH w/ 2 3/8" tbg. & squeeze 100 sx Class "B" cement @ 900 psi. POH & lay down tbg. Flange up wellhead & nipple down BOP.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED DeW B... TITLE Area Superintendent DATE 8-12-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

ACCEPTED FOR RECORD

AUG 17 1981

\*See Instructions on Reverse Side

BY RB

NMCC