


(SUBMIT IN TRIPLICATE)

Land Office \_\_\_\_\_

Lease No. S.F. 079602Unit L. L. McConnellUNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

L. L. McConnellWell No. 2 is located 1135 ft. from [S] line and 985 ft. from [E] line of sec. 31SE 1/4 Section 31

(1/4 Sec. and Sec. No.)

23E

(Twp.)

1E

(Range)

T. 1 N. R. 2 E.

(Meridian)

Undesignated

(Field)

Mc Auliffe

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 7129 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded: May 23, 1956.

Ran 5 joints 10-3/4" casing set at 170' & cemented  
with 150 sacks regular cement w/2% calcium chloride  
added. Tested casing with 500# pressure for 30 minutes.  
Pressure held.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be started.

Company SEELY OIL COMPANYAddress Box 400,Farmington, New MexicoBy J. E. CooperTitle District Engineer