



Budget Bureau No. 42-R358.4.  
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. S.F. 079602  
Unit L.L. McConnell

**SUNDRY NOTICES AND REPORTS ON WELLS**

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Perforate</u>
	<u>Sand-Crue</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

L. L. McConnell

June 11, 1956

Well No. 2 is located 1135 ft. from S line and 985 ft. from E line of sec. 31

SE 1/4 Section 31  
(1/4 Sec. and Sec. No.)

25N  
(Twp.)

3E  
(Range)

N. H. P. M.  
(Meridian)

Undesignated  
(Field)

Rio Arriba  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 7129 ft.

**DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated from 3430' - 3493' with 4 (9/16) Line Well bullets per foot, for total of 252 shots.

Sand-fraced with 50,000' sand, 43,000 gals. water. Flushed with 10,080 gals. water. Breakdown pressure 2000', Max. 1100', Min. 1100', time of treatment 24 min., injection rate 51.8 bbls. per minute. Shut in 4 hrs. pressure 500'

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SEELY OIL COMPANY

Address Box 426

Farmington, New Mexico

By

P. E. Cooper

Title

District Foreman