



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No.

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Report of perforations and sand- fracing

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

L. L. McConnell

May 23, 1956

Well No. 3 is located 1157 ft. from [N] line and 2700 ft. from [E] line of sec. 21

34/4 Section 21
(1/4 Sec. and Sec. No.)25N
(Twp.)3W
(Range)T. 4 N. P. 4 E.
(Meridian)Undesignated
(Field)Rio Arriba
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7257 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated with 4-15/32 Lane-Wells bullets per foot from
3546' - 3605' for a total of 236 shots.

Treated through perforations with 50,000 gal. sand and 48,300
gallons water, using 150 bbls to flush. Breakdown pressure,
2300 psi - treating pressure 1100 psi to 1500 psi. Injection rate,
53.3 bbls/min. Time of treatment 23 minutes. Shut in pressure
after treatment 600 psi, shut in 6 hrs. Well pressure to 0 psi.

I understand that this plan of work must receive approval in writing by the Geological Survey before operation may be commenced.

Company SHELBY OIL COMPANY

Address Box 426,

Farmington, New Mexico

By

Title District Foreman



