

(SUBMIT IN TRIPLICATE)

Indian Agency Hicarilla

UNITED STATES

Tribal

DEPARTMENT OF THE INTERIOR

Allottee Hicarilla "B"

GEOLOGICAL SURVEY

Lease No. Contract #49  
Tract #127

# SUNDRY NOTICES AND REPORTS ON WELLS

|   |  |  |          |
|---|--|--|----------|
| NOTICE OF INTENTION TO DRILL                |  | SUBSEQUENT REPORT OF WATER SHUT-OFF        |          |
| NOTICE OF INTENTION TO CHANGE PLANS         |  | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF  |  | SUBSEQUENT REPORT OF ALTERING CASING       |          |
| NOTICE OF INTENTION TO REDRILL OR REPAIR    |  | SUBSEQUENT REPORT OF REDRILLING OR REPAIR  |          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE     |  | SUBSEQUENT REPORT OF ABANDONMENT           |          |
| NOTICE OF INTENTION TO PULL OR ALTER CASING |  | SUPPLEMENTARY WELL HISTORY                 |          |
| NOTICE OF INTENTION TO ABANDON WELL         |  | <u>Report of Perforations</u>              | <u>X</u> |
|   |  | <u>Report of Sand-Oil Frasing</u>          | <u>X</u> |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 1, 1958

Hicarilla "B"  
Well No. 10 is located 660 ft. from [S] line and 660 ft. from [E] line of sec. 32  
SE/4-SE/4 Section 32 29N 9W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Grove-Gallup Rio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)


The elevation of the derrick floor above sea level is 6175 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Perforated  $\frac{5}{8}$ " casing 6081-82' with 4 Welox jet shots. Perforated  $\frac{5}{8}$ " casing 5983-95', 6000-04', 6019-30', 6042-61', 6077-81' with 4 Welox jet shots per ft. Total of 90', 200 shots.

Frased Gallup formation, down  $\frac{5}{8}$ " casing & 2" tubing, thru  $\frac{5}{8}$ " casing perfor. 5983-95', 6000-04', 6019-30', 6042-61' & 6077-82' with 30,000' 20-40 sand & 42,630 gals. lss. oil. BHP 3000', Max. TP 3300', Min. TP 2900', Inj. Rate 30.3 BPM. Shut in pressure in 5 min. 800', left well shut in 2 hrs. & pressure dropped to 100'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY  
Box 426  
Address Farmington, New Mexico

By (Signed) P. E. Cosper

Title District Superintendent

01

