

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such purposes.

5. Lease Designation and Serial No.

NM 015016

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal - G #1

9. API Well No.

30039 05-734

10. Field and Pool, or Exploratory Area

Gallup/P.C.

11. County or Parish, State

Rio ARABA, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Joseph B. Gould Interest

3. Address and Telephone No.

101 Convention Center Dr., Suite #675, Las Vegas, NV 89109

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Section 31, T25N, R01W (N/E 1/4)

1826' FNL, 1724' FEL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Plugged well per procedures Approved on 2-24-2000

2. See Attached Plugging Report



14. I hereby certify that the foregoing is true and correct

Signed

Nathan Langford

Title

PGA Supervisor

Date

2-29-00

(This space for Federal or State office use)

Approved by

[Signature]

Title

Per. Eng.

Date

4/4/00

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side



Key Energy Services, Inc.

Four Corners Division
5651 US Highway 64
P.O. Box 900
Farmington, NM 87499

Phone: 505-327-4935
Fax: 505-327-4962

**PLUG & ABANDON
CEMENT SERVICE REPORT**

WELL NAME: FEDERAL G #1

TOTAL PLUGS SET: 3

DATE STARTED: 03-20-00

TOTAL SACKS USED: 150 SX

DATE COMPLETED: 03-27-00

BLM WITNESS: A. YEPA
OPERATOR WITNESS: N/A

MOL AND RU. HELD SAFETY MEETING FOR EVERYONE ONE LOCATION. NU RELIEF LINE AND BLED DOWN WELL. ND WELLHEAD AND NU BOP. TESTED BOP.

**PLUG #1 (OJO ALAMO, PICTURED CLIFFS, 3230' – 3544');
RIH WITH 5 ½" GAUGE RING TO 3550'. POH. RIH WITH 5 ½" CIBP AND SET AT 3544'. PU AND STRAPPED IN HOLE, OPEN ENDED WITH 2 3/8" WORK STRING AND TAGGED TOP OF CIBP. CIRCULATED HOLE CLEAN WITH WATER. PRESSURE TESTED CASING TO 500 PSI AND HELD GOOD FOR 10 MINUTES. BALANCED 36 SX CLASS B CEMENT PLUG INSIDE CASING. POH.**

**PLUG #2 (NACIMIENTO, 1570' – 1670');
RIH AND PERFORATED SQUEEZE HOLES AT 1670'. POH. PU AND RIH WITH 5 ½" RETAINER AND SET AT 1620'. ESTABLISHED INJECTION RATE INTO PERFORATIONS WITH WATER AT 2 BPM WITH 1200 PSI. MIXED 63 SX CLASS B CEMENT AND PLACED 51 SX BELOW AND 12 SX ABOVE THE RETAINER. SQUEEZING TO 250 PSI. POH.**

**PLUG #3 (SURFACE, SURFACE SHOE, 0' – 150');
RIH AND PERFORATED SQUEEZE HOLES AT 150'. ESTABLISHED CIRCULATION TO SURFACE WITH WATER OUT THE BRADON HEAD. MIXED 51 SX CLASS B CEMENT TO CIRCULATE GOOD CEMENT TO SURFACE.**

RD FLOOR AND DUG CELLAR. CUT OFF WELLHEAD BELOW SURFACE CASING COLLAR. INSTALLED DRY HOLE MARKER. RD RIG AND MOL.


NATHAN E. CRAWFORD
P&A SUPERVISOR