

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3360, Casper, Wyoming 82602

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Plug back and hold ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

Contract No. 34

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla "C"

9. WELL NO.

22

10. FIELD OR WILDCAT NAME

Otero Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33 - T25N-R5W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6783' GR; 6793' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well is depleted Gallup producer shut-in since 5-27-74. We propose to plug back to the base of the Chacra sand, as outlined below, and hold pending evaluation of recent Pictured Cliffs - Chacra recompletions in the area. Should conditions merit a recompletion attempt, a procedure will be forthcoming.

Present cement behind 5 1/2" casing is from TD to 5270' and from 3926' to 2090'.
First Plug - 40 sx of cement covering the Gallup perfs @ 6149'-6253' and filling up to approximately 6035'.

Second Plug - Perforate 5 1/2" casing and spot 100' cement plug inside and outside from 5150' up to 5050'.

Third Plug - Perforate 5 1/2" casing and spot 100' cement plug inside and outside from 4420' up to 4320'.

Fourth Plug - Spot 100' cement plug inside 5 1/2" casing from 3926' up to 3860'.

Subsurface Safety Valve: Manual and Type - A 9 mmg mud will be spotted between all plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED W. E. Barrick TITLE Superintendent DATE Mar 25 1980

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APPROVED


MAR 25 1980

CARL A. BARRICK
ACTING DISTRICT ENGINEER

TEMPORARY ABANDONMENT

EXPIRES MAR 26 1981

*See Instructions on Reverse Side



MAR 21 1980

U. S. GEOLOGICAL SURVEY
DENVER, COLO.