

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
Getty Oil Company
3. ADDRESS OF OPERATOR  
P.O. Box 3360, Casper, Wyoming 82602
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE  
Contract No. 34
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Jicarilla "C"
9. WELL NO.  
22
10. FIELD OR WILDCAT NAME  
Otero Gallup
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 33-T25N-R5W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB. AND WD)  
6783'GR 6793'DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spotted 25 sx Class "B" @ 3760' to 3539', 2820' to 2599', and 2220' to 1999'. Pumped 450 sx Class "B": circulated cmt outside fo 5½" casing up to bradenhead and left 5½" csg full of cmt. Set standard abandoned-well marker and released rig @ 9:30 A.M., 10-7-80. These cement plugs were in addition to those plugs reported on our subsequent report of: Plug back and hold (see attached).

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. E. Galt TITLE \_\_\_\_\_ DATE \_\_\_\_\_

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

REC-11  
AER 19 1984  
OIL CON. DIV.  
DIST. 3