

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	A graduated		Purpose
							From—	To—	
10-3/4"	32.75	8	7-40	330	Front Collar	6068	6074	6074	Production
5-1/2"	15.75	8	7-40	330	Front Collar	6096	6112	6112	Production
						6122	6144	6144	Production
						6160	6168	6168	Production

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
10-3/4"	344	300	Halliburton		
5-1/2"	6226	739 (2-stage)	Halliburton		
Temperature survey on 1st stage indicated top of cement behind 54" OD casing at 4906'.					
Temperature survey on 2nd stage indicated top of cement behind 54" OD casing at 1683'.					

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____
 Adapters—Material _____ Size _____

SHOOTING RECORD

Well was Sand/Oil Frased

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
Frased Gallup formation w/25,000# 20/40 sand & 31,564 gals. lse. oil by Halliburton, using 36 rubber frce balls. BDF 2000#, Max. TP 3400#, Min. TP 2500#, Inj. rate 30.5 BPM, Standing pressure 1150#.						

TOOLS USED

Rotary tools were used from _____ feet to 6227 _____ feet, and from _____ feet to _____ feet
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

April 28, 1959 _____ Put to producing _____ April 13, 1959 _____
 The production for the first 24 hours was _____ 31 barrels of fluid of which 99.8% was oil; .2% emulsion; 0% water; and _____ % sediment. GOR 3761:1 Gravity, °Bé. 41.7
 If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Nichols Drilling Company, Inc., Driller _____, Driller
 _____, Driller _____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	2710	2710	Sand & Shale
2710	2765	55	Sand & Shale - Top Pictured Cliffs 2710'
2765	3539	774	Sand & Shale - Top Lewis 2765'
3539	4900	1361	Sand & Shale - Top Chacra Sand 3539'
4900	5073	173	Sand & Shale - Top Point Lookout 4900'
5073	6000	927	Sand & Shale - Top Mancos 5073'
6000	6096	96	Sand & Shale - Top Gallup 6000'
6096	6227	131	Sand & Shale - Top Middle Gallup 6096'
Tops by Schlumberger Induction-Electric Log.			
OF LENGTH		6227'	
LUGS & BACK TOTAL DEPTH		6191'	

(OVER)