


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. AP 079602
Unit L. L. McConnell



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	U. S. GEOLOGICAL SURVEY FARMINGTON, NEW MEXICO	SUBSEQUENT REPORT OF WATER SHUT-OFF	<u>Production</u>	<u>X</u>
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING		
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT		
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON WELL		<u>Report of Perforations</u>		<u>X</u>
		<u>Report of Sand Freeing</u>		<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 2, 1958

L. L. McConnell
Well No. 9 is located 1110 ft. from S line and 970 ft. from E line of sec. 29
1/4-SE/4 Section 29 25N 34 N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Blaine (P.C.) Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7344 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran & set $5\frac{1}{2}$ " casing at 3620' & cemented w/50 sks. reg. cement & 50 cu. ft. strata crite, 25 Gal. Ran temperature survey by B&E Service Co. & found top of cement behind $5\frac{1}{2}$ " casing at 3925'.

Perforated $5\frac{1}{2}$ " casing 3761-42' w/Lane Wells type "E" bullets to test cement job. Cement job tested O.K. Perforated $5\frac{1}{2}$ " casing 3690-3728' & 3744-61' w/4 Lane Wells type "E" bullets. Total perfs. 56', 224 holes.

Pressed Pictured Cliffs formation, down $5\frac{1}{2}$ " casing, thru $5\frac{1}{2}$ " casing perfs. 3690-3728' & 3744-62' by Dowell w/40,000# 20-40 sand & 40,000 gals. water. BDP 1100#, Max. TP 1900#, Min. TP 1800#. Press. dropped to zero when pumps shut down. Inj. rate 60 BPM. Time of treatment 28 min.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY DRILLING
Box 486
Address Farmington, New Mexico
By Edward E. Rogers
Title District Superintendent