

Form 0-881b  
APPROVED  
OCT 9 1956  
JERRY W. LONG  
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R359.4  
Approval expires 12-31-60.

Indian Agency **Sanilla Apache**  
Cont. **79** Sheet **718**

Allottee **Sanilla Apache "A"**  
Lease No. \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 16, 1956, 19

Well No. **5** is located **880** ft. from **1/4** line and **990** ft. from **1/2** line of sec. **25**  
**SE/4 SE/4 Sec. 25** **T-25-N** **R-5-N** **DEM**  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Undesignated** **Rio Arriba** **New Mexico**  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **7000** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 12-1/4" hole @ 12:00 noon 5-14-56 & drilled to 232' @ 9:00 p.m. 5-14-56. Ran 5 jts 8-5/8" cas., set @ 227' & cemented w/125 sks reg. cement, mixed 2% gal. 2% cal. chloride. Pumped plug to 200' @ 12 midnight 5-14-56. Cement circulated. W.O.C. Tested cas. before drilling cement w/1000' & after drilling cement w/500' held OK. Started 7-7/8" hole @ 5:15 p.m. 5-16-56 and drilled to 7743' 7-1-56. 7-4-56 Ran 56 jts 5-1/2" 17# cas & 126 jts 5-1/2" 15.5# cas & set @ 6630' & cement w/150 sks reg. cement mixed 2% gal. Pumped plug to 6606' @ 5:30 a.m. 7-4-56. Max. press 1200' & bled back to 500'. W.O.C. Ran temp. survey & found top of cement @ 6080' outside of 5-1/2" cas. - 61# fill. Tested 5-1/2" cas w/1500' after drilling out - held OK. Continuing w/completion operations.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **AMERADA PETROLEUM CORPORATION**  
 Address **Box 535**  
**Farmington, New Mexico**  
 RECEIVED  
 OCT 10 1956 By **W. G. Smith**  
 OIL CON. COM.  
 DIST. 3 Title **Form 884**

