Fo	A Feb. 1	951)	P	R	OVE	ED
			oc	2	1956	
	ACT	J E	E A R	Y V	. LONG CT ENGI	NEER

(SUBMIT IN TRIPLICATE)

## UNITED STATES EPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Office	Sm	ita Fe
Lease	No.S.	F.	079602
٠.	T	Ŧ	Martin 19

SUNDRY	NOTICES A	AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL.		SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE		
NOTICE OF INTENTION TO TEST W		
IOTICE OF INTENTION TO RE-DRIL IOTICE OF INTENTION TO SHOOT		
OTICE OF INTENTION TO SHOOT		
NOTICE OF INTENTION TO ABANDO		·•
(INDI	CATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
L.L.McConnell		, 19, 19, 19,
ell No. 6 is loc	cated <b>1570</b> ft. from	m. $\{S\}$ line and 1735 ft. from $\{E\}$ line of sec. 10
(1/ Sec. and Sec. No.)	251 (Twp.)	(Kange) (Meridian)
(Field)	Rie Arribe	y or Subdivision) (State or Territory)
(= 11117)		, , , , , , , , , , , , , ,
e elevation of the derric		
	DETA	AILS OF WORK
	ing points, and all	sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- l other important proposed work)
Ran 117 jnts. of 5 Cemented with 200 : Perforated 5-1/2" oper foot for total	sks. reg. camer casing from 363 of 243 shote.	55 Casing - set at 3774° t.  0° to 3742° w/4 (9/16) Schlumberger bullets  3680° - 3742′ - w/50,000% sand - 44,300 gals.
Ran 117 jnts. of 5 Cemented with 200 : Perforated 5-1/2" oper foot for total Sand fraced throughwater. 150 bbls. 1 55.4 RFM.	ing points, and all  1/2" OD 14/ J-  sks. reg. camer  casing from 363  of 248 shots.  h perforations  water flush. B	55 Casing - set at 3774° t.  0' to 3742' w/4 (9/16) Schlumberger bullets  3680' - 3742' - w/50,000# sand - 44,300 gals.
Ran 117 jnts. of 5 Comented with 200 : Perforated 5-1/2" oper foot for total Sand fraced through water. 150 bbls. 1 55.4 BPM.	ing points, and all  1/2" OD 14/ J-  sks. reg. camer  casing from 363  of 248 shots.  h perforations  water flush. B	o' to 3742' w/4 (9/16) Schlumberger bullets  3680' - 3742' - w/50,000" sand - 44,300 gals.  D 2000' - 1500' - Min. 1600'. Inj. rat
Ran 117 jnts. of 5 Cemented with 200 : Perforated 5-1/2" per foot for total Sand fraced through water. 150 bbls. 1 55.4 BPM.	ing points, and all  1/2" OD 14/ J-  sks. reg. camer  casing from 363  of 248 shots.  h perforations  water flush. B	55 Casing - set at 3774' t.  O' to 3742' w/4 (9/16) Schlumberger bullets  3680' - 3742' - w/50,000# sand - 44,300 gals.  D 2004 - Min. 1600#. Inj. rat