Vangge

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency 51 Contract 69	earilla Trest	Aribel Ac
Allottee		
Lease No. Jiear	illa Ap	ache %"

NOTICE OF INTENTION TO DOUG		SUBSEQUENT REPORT OF WATE	SHIIT-OFF
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PLAI	NS	SUBSEQUENT REPORT OF SHOO	
NOTICE OF INTENTION TO CHANGE PLAI NOTICE OF INTENTION TO TEST WATER	i	SUBSEQUENT REPORT OF ALTE	
OTICE OF INTENTION TO REDRILL OR	i	SUBSEQUENT REPORT OF REDR	
IOTICE OF INTENTION TO SHOOT OR AC	CIDIZE	SUBSEQUENT REPORT OF ABAN	DONMENT
IOTICE OF INTENTION TO PULL OR ALT	TER CASING	SUPPLEMENTARY WELL HISTOR	Kr 419
OTICE OF INTENTION TO ABANDON WE	IL		MAI COLCAL
/INDIA ***	ABOVE BY CHECK MARK	VATURE OF REPORT NOTICE OF OTHER	PRATANI S. TON
(INDICATE A	rbove by Check Mark i	ATORE OF REPORT, NOTICE, OR OTHE	FARRINGTON
		May 10, 1956	10 thu.
No. 4 is locat	ted 990 ft. from	n line and 990 ft	rom ine of sec.
Il 140 18 10cat	tedtt. Ifo	$n \left\{ S \right\}$ line andft.	rom Mine of Sec
E/4 of 85/4 Sec. 26	25-1	5-X HWM	
(½ Sec. and Sec. No.)	(Twp.)	(Range) (Meridian	Annual Manual Manual
(Field)	San Juan	r Subdivision)	(State or Territory)
ne elevation of the derrick fl	loor above sea lev	el is tt.	
	DETAI	LS OF WORK	
		<del>-</del> - ·	
te names of and expected depths to o		<del>-</del> - ·	asings; indicate mudding jobs, o
		<del>-</del> - ·	asings; indicate mudding jobs, o
4000° T.D. 3981°	bjective sands; show size ing points, and all of DOD	s, weights, and lengths of proposed of the important proposed work)	
4000° T.D. 3981°. Ren 95 1te 5-1	bjective sands; show size ing points, and all of DOD	<del>-</del> - ·	asings; indicate mudding jobs,
4000° T.D. 3961° Ran 95 Jts 5-1 res, squart mi	bjective sands; show size ing points, and all of DOD	s, weights, and lengths of proposed of the important proposed work)  paging, set a 3909* (	comented W/350 s W/mex. pump proces
4000° T.D. 3981°. Ren 95 Jte 5-1	bjective sands; show size ing points, and all of DOD	s, weights, and lengths of proposed of the important proposed work)	
4000° T.D. 3961° Ran 95 Jts 5-1 res cenert mi	bjective sands; show size ing points, and all of DOD  /2" OD 15-5-6  xed 25 gel.  C. Ram temp	s, weights, and lengths of proposed of the important proposed work)  sacing, set 0 3989*  ranged plug to 3945*	womented W/350 at W/max. pump press of top of counts of wing W/1000/ before
4000° T.D. 3961° Ran 95 Jts 5-1 res cenert mi	bjective sands; show size ing points, and all of DOD  /2" OD 15-5-6  xed 25 gel.  C. Ram temp	s, weights, and lengths of proposed of the important proposed work)  seeing, set 0 3989*  respect plug to 7945*  reture survey a four 845 fill. To sted o	s commuted W/350 st W/max. pump press of top of commute wing W/1000/ befor ng with completion
Ran 95 jts 5-1 reg. sement mi of 800%, N.O. of 5-1/2" east after drilling	bjective sands; show size ing points, and all of DOD  /2" OD 15-5-6  xed 25 gel.  C. Ram temp	s, weights, and lengths of proposed of the important proposed work)  pacing, set a 3969*  Amped plug to 3945*  Pature survey & four 845 fill. Ested on the latest continued to	s commuted W/350 st W/max. pump press of top of commute wing W/1000/ befor ng with completion
Ran 95 jts 5-1 res. sement mi of 800*, N.O. of 5-1/2" ensi after drilling	bjective sands; show size ing points, and all of DOD  /2" OD 15-5-6  xed 25 gel.  C. Ram temp	s, weights, and lengths of proposed of the important proposed work)  pacing, set a 3969*  Amped plug to 3945*  Pature survey & four 845 fill. Ested on the latest continued to	s commuted W/350 st W/max. pump press of top of commute wing W/1000/ befor ng with completion
Ren 95 jts 5-1 res cement mi of 800s, N.O. of 5-1/2" east after drilling	bjective sands; show size ing points, and all of DOD  /2" OD 15-5-6  xed 25 gel.  C. Ram temp	s, weights, and lengths of proposed of the important proposed work)  pacing, set a 3969*  Amped plug to 3945*  Pature survey & four 845 fill. Ested on the latest continued to	s commuted W/350 st W/max. pump press of top of commute wing W/1000/ befor ng with completion
Ran 95 jts 5-1 res. sement mi of 800*, N.O. of 5-1/2" ensi after drilling	bjective sands; show size ing points, and all of DOD  /2" OD 15-5-6  xed 25 gel.  C. Ram temp	s, weights, and lengths of proposed of the important proposed work)  pacing, set a 3969*  Amped plug to 3945*  Pature survey & four 845 fill. Ested on the latest continued to	s commuted W/350 st W/max. pump press of top of commute wing W/1000/ befor ng with completion
Ran 95 jts 5-1 res. cement mi of 800%, N.O. of 5-1/2" east after drilling work. Drill test.	bjective sands; show size ing points, and all of DOD  /2" OD 15.55  xed 25 gol.  C. Rem tempting 4 2105 or consert a plu cut to 3981.	s, weights, and lengths of proposed ther important proposed work)  passing, set 0 3969* 6  passing to 3945*  return survey & four 845 fill, Tested as  s, held CK, Continue perforate Leventame	W/mex. pump process id top of commit or seing W/1000/ befor ing with completion Coetical, sand-fre
Ran 95 jts 5-1 res. cement mi of 800%, N.C. of 5-1/2" east after drilling work. Drill test.	bjective sands; show size ing points, and all of DOD  /2" OD 15.55  xed 25 gol.  C. Rem tempting 4 2105 or consert a plu cut to 3981.	s, weights, and lengths of proposed ther important proposed work)  passing, set 0 3969* 6  passing to 3945*  return survey & four 845 fill, Tested as  s, held CK, Continue perforate Leventame	W/max. pump process id top of counts of soing W/1000/ befor ing with completion Section, sand-free or operations may be comine
Ran 95 jts 5-1  wege coment mit of 800%, N.O. of 5-1/2" east after drilling weaks. Drill test.	bjective sands; show size ing points, and all of DOD  /2" OD 15.55  xed 25 gol.  C. Rem tempting 4 2105 or consert a plu cut to 3981.	s, weights, and lengths of proposed ther important proposed work)  pacing, set a 3989* ( respect plug to 3945*  return survey & four 845 fill. Ested of  perforate Leventana	W/mex. pump process id top of commit or seing W/1000/ befor ing with completion Coetical, sand-fre
Ran 95 jts 5-1 reg. coment mi of 800%, N.O. of 5-1/2" cost after drilling work. Drill test.	bjective sands; show size ing points, and all of DOD  /2* OD 15.5*  xed 25 gol.  C. Rem tempting # 2105* OF centers to 3981*,  must receive approval in the TROLLEUM OCRE	s, weights, and lengths of proposed ther important proposed work)  pasing, set 0 3969* ( passed plug to 3945*  pasture survey a four 845 fill. Tested a 8. held CK. Continue perforate Leventama  writing by the Geological Survey be	W/max. pump process id top of counts of soing W/1000/ befor ing with completion Section, sand-free or operations may be comine
Ram 95 jts 5-1  Wes coment mit of 800%, N.O. of 5-1/2" east after drilling weak, Drill test.	bjective sands; show size ing points, and all of DOD  /2* OD 15.5*  xed 25 gol.  C. Rem tempting # 2105* OF centers to 3981*,  must receive approval in the TROLLEUM OCRE	s, weights, and lengths of proposed ther important proposed work)  pacing, set a 3989* ( respect plug to 3945*  return survey & four 845 fill. Ested of  perforate Leventana	W/mex. pump processed top of counts of selection, send-from JUN 22 1956 OIL CON. COM.
Ran 95 jts 5-1  Ran 95 jts 5-1	bjective sands; show size ing points, and all of DOD  /2* OD 15.5*  xed 25 gol.  C. Rem tempting # 2105* OF centers to 3981*,  must receive approval in the TROLLEUM OCRE	s, weights, and lengths of proposed ther important proposed work)  pasing, set 0 3969* ( passed plug to 3945*  pasture survey a four 845 fill. Tested a 8. held CK. Continue perforate Leventama  writing by the Geological Survey be	W/mex. pump processed top of commit of sing W/1000/ beforing with completion continuous and free continuou
Ran 95 jts 5-1  Ran 95 jts 5-1	bjective sands; show size ing points, and all of DOD  /2* OD 15.5*  xed 25 gol.  C. Rem tempting # 2105* OF centers to 3981*,  must receive approval in the TROLLEUM OCRE	s, weights, and lengths of proposed ther important proposed work)  pasing, set 0 3969* ( passed plug to 3945*  pasture survey a four 845 fill. Tested a 8. held CK. Continue perforate Leventama  writing by the Geological Survey be	W/mex. pump processed top of counts of selection, send-from JUN 22 1956 OIL CON. COM.
Ram 95 jts 5-1  was coment mi of 500%, N.O. of 5-1/2" east after drilling work. Drill test.	bjective sands; show size ing points, and all of DOD  /2* OD 15.5*  xed 25 gol.  C. Rem tempting # 2105* OF centers to 3981*,  must receive approval in the TROLLEUM OCRE	s, weights, and lengths of proposed ther important proposed work)  pasing, set 0 3969*  Pasped plug to 3945*  Pasture survey a four  845 fill. Tested of  8, held CK. Continue  perforate Leventama  writing by the Geological Survey be  RATION  By  By  By  By  By  Continue  By  By  By  By  By  By  By  By  By  B	W/max. pump processed top of commit of commit of commit of completion ag with completion commits of commit of commit of commits of commit of committees and commit of
Ran 95 jts 5-1  was coment mi of 800%, N.C. of 5-1/2" cast after drilling work. brill test.	bjective sands; show size ing points, and all of DOD  /2* OD 15.5*  xed 25 gol.  C. Rem tempting # 2105* OF centers to 3981*,  must receive approval in the TROLLEUM OCRE	s, weights, and lengths of proposed ther important proposed work)  pasing, set 0 3969* ( passed plug to 3945*  pasture survey a four 845 fill. Tested a 8. held CK. Continue perforate Leventama  writing by the Geological Survey be	W/max. pump promised top of counts of the counts of counts of the counts

