DC-395 / Que 1/24/57

KELLY OIL COMPANY

TULSA 2, OKLAHOMA

Danuary 11, 1957

(Company 1)

New Mexico Oil Conservation Commission P. O. Box 871 Santa Fe, New Mexico

Gentlemen:

Please consider this letter as Skelly Oil Company's application to dual complete its Jicarilla "C" Well No. 11 and in support thereof provides as follows:

- 1. That the applicant is the operator of this lease which contains 2560 acres and is described as the S/2 Section 21 and S/2 Section 22; all of Section 27 and 28; N/2 Section 33 and N/2 of Section 34, all in Township 25 North and Range 5 West, Rio Arriba County.
- 2. That the applicant's Jicarilla "C" Well No. 11 is located 1450' from the South line and 1190' from the West line of Section 27-25N-5W. Rio Arriba County, New Mexico.
- 3. That the applicant dually completed the well in the following manner:
 - Perforated 5-1/2" casing from 2723' to 2758' in the Pictured Cliffs.
 - b. Perforated 5-1/2" casing from 3583; to 3602; in the Lewis Sand.
 - c. Set production type packer at 3561°. Landing nipple was set on top of packer at 35609 with the sidedoor choke set in landing nipple.
 - d. Will produce Pictured Cliffs gas through annulus of 5-1/2" casing and Lewis Sand gas through 2" tubing.
- 4. That the granting of this application to produce this well as a dual completion from the Pictured Cliffs and Lewis Sand is in the interest of conservation and the protection of correlative rights.

- 5. That the manner and method of this dual completion is mechanically feasible and practical.
- 6. That a diagramatic sketch showing the producing intervals and the physical equipment used in dualling the well is attached.
- 7. That a plat showing the above described lands and all offset properties, indicating well locations and lease ownership to the best of our knowledge is attached.
- 8. That all offset operators are hereby notified by a copy of this application.

WHEREFORE, PREMISES CONSIDERED, applicant requests that the Secretary of the Commission grant Administrative approval to produce this well as a dual completion.

Respectfully submitted,

Skelly OIL COMPANY

GWS:zmr

George W. Selinger

STATE OF OKLAHOMA)

SS
COUNTY OF TULSA)

Personally appeared George W. Selinger, of Skelly Oil Company, Tulsa, Oklahoma, who states after being duly sworn upon oath that this instrument is true and correct to his best knowledge and belief.

					-	A	ffiar	nt				
Subscribed	and	sworn	to	befor e	me	this	the		day	of	January,	1957.
						No	otar	y Public				

cc-Skelly Oil Company Mr. P. E. Cosper Box 426 Farmington, New Mexico

> United States Geological Survey Box 965 Farmington, New Mexico

Southern Union Gas Company Burt Building Dallas, Texas

Superior Oil Company 218 West Illinois Street Midland, Texas

New Mexico Oil Conservation Commission 120 East Chaco Street Aztec, New Mexico

Amerada Petroleum Corporation Box 2040 Tulsa, Oklahoma

Stanolind Oil & Gas Company Box 1410 Fort Worth, Texas

RIO ARRIBA COUNTY NEW MEXICO

R6W			R5	SW .			
是. Superior	A-revada	Amerasa \$F-2	Ame-ada	§*gro∵nd	Shana ili ∰1 03	Shandi no ☆ 4	
13	18	17	16	ক্ষত 15	14	\$2.4 \3	
\$ 7.		☆ 1		\$ 7	\$2	\$\$	
Superior \$2-24	03-26	Superior	Amerada	America	Ŝtano rnd	5+anolina	
2.4	19	数部 2 20	21	22 5**	☆8 - 23 · · · -	#3 24	
\$≱1.24		C.Silver 67:3\$	484 46187 357 4	· 57.10 ##.	* 3	Ø 2	T
u A Hughes	900 6 7.37	Superian	444 - 444 克 ²	31₩	Amerada	Amerada	25 N
25	30	29	28	27	2.6	4 -5-55 25	
			²²⁵ 2 ²⁵ 3		-	4.5	
marien Sc Per	" F"	45614	1 .	///a°C"	Ame-283	Amenada	
51 Pass 3 6	31	32	33 PW 3	2·27·51 34	35	Stansono	
OB STEAL Malco			300 00 00 00 00 00 00 00 00 00 00 00 00	0			
H276: 30120A		F.*	So Union	So Union	5*ana ind	Ŝeano kaŭ	_
1	6	<u> </u>	4	Rustina 3	2.	1	
PetriAtias Oliá	54. Jicarilla ©1	"B"		1 #M 5 : 10 55			T
Superior	iju P	5*	R.S. 9 Ø 8-A 2525'	Se din th	Sa Union \$46	5+anolind	24 N
12	∳ è 7	8	Censes	20-20-	Lowry 11	12	
☆ 1·2	₽ 4	₽ 2			♦ 79131 1.8		

Scale !" Mile

JICARILLA "C" No. 11 1450' FROM SOUTH AND 1190' FROM WEST LINES SECTION 27-25N-5W RIO ARRIBA COUNTY NEW MEXICO

	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Top of cement 2310'
Picture Cliffs		2723'-58'
Lewis Sand	4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4	
		. 5½" Csg. Set at 3665' with 400 sx. Cement.
	T.D. 3670'	