

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

El Paso Exploration Company

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1760'S, 1150'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

SUBSEQUENT REPORT OF:

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M. (NOT

15 ELEVATIONS (SHOW DF, KDB, AND WD)
7249' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

CIL CONL COM.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MOL & RU. Run string of 1 1/4" IJ tubing in well and circulate. Spot a 10 sx (12 ft³) cement plug on perforations.

Displace 6 sx through the perforations leaving a cement plug from 3352-3494'.

Perforate 2 squeeze holes @ base of Ojo Alamo (3060'). Spot a 46 sx (39 ft³) cement plug to cover Ojo Alamo from 2830-3060'. Displace 40 sx through perforations. * Perforate 2 squeeze holes @ 105'. Spot a 31 sx (26 ft³) cement plug to fill the surface casing from 5' to 105'.

Displace 28 sx through perforations.

Spot a 10 sx (12 ft³) cement plug @ the surface and install a dryhole marker.

Work expected to be completed in July 1981.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct,

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Production Engineer DATE June 25, 1981

APPROVED (This space for Federal or State office use)

APPROVED BY
CONDITIONS OF

JAMES F. SIMS
DISTRICT ENGINEER

TITLE _____

NMOCC

FEDERAL SURFACE

Attachment to Notice of
Intention to Abandon

U. S. GEOLOGICAL SURVEY
P. O. Box 959
Farmington, New Mexico 87401

8-5-81

Re: Permanent Abandonment

Well: #10 Jicarilla D

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases".
2. The Farmington office (telephone (505) 325-4672) is to be notified in sufficient time for a representative to witness all plugging operations.
3. Blowout prevention equipment is required.
4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Bureau of Land Management for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
5. The surface management agency is to be notified when surface rehabilitation is complete.

- * 6. The following modifications to your plugging program are to be made (when applicable):

- a) Spot cement plug from 3319' to 3219'
- b) Perforate 2 7/8" casing at 157' and place cement plug inside and outside casing from 157' to 57'

Office Hours: 8:00 A.M. to 5:00 P.M.
Farmington Personnel to be notified:

Home Telephones:

Ray Swanson: Petroleum Engineering Technician - 325-8189
Fred Edwards: Petroleum Engineering Technician - 325-7885
Ken Baker: Petroleum Engineering Technician - 327-2170

