

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Alamogordo Indian Reservation
Cont. Pl. Tr. 86
Allottee _____
Lease No. Alamogordo

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

RECEIVED

JUL 15 1957

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 8

19 57

Well No. 2-3 is located 1750 ft. from N line and 1750 ft. from W line of sec. 29

<u>N 29</u> (1/4 Sec. and Sec. No.)	<u>29N</u> (Twp.)	<u>4N</u> (Range)	<u>N.M.P.M.</u> (Meridian)
<u>So. Hance P.C.</u> (Field)	<u>Rio Arriba</u> (County or Subdivision)	<u>New Mexico</u> (State or Territory)	

The elevation of the derrick floor above sea level is 7000 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-30-57. T.D. 3315'.
Run 28 lbs. 5-1/8", 15.5#, 5-55 casing (3304') set at
3314' with 90 sacks regular cement, 90 sacks Pozmix, 45 Gal.
followed by 90 sacks regular cement.
Hold 1000# for 30 minutes.
Top of cement by temperature survey at 2850'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Co.

Address Box 997

Farmington, N.M.

By Original Signed D. C. Johnston

Title Petroleum Engineer

