

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Contract No. 34

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla "C"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

S. Blanco - P.C.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-T25N-R5W

12. COUNTY OR PARISH

13. STATE

Rio Arriba

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 3360, Casper, WY 82602

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

1295' FNL & 1295' FWL Sec. 28-T25N-R5W
(NW/4 NW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

6608' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well is a former Pictured Cliffs producer. It was drilled through the Mesaverde formation, but a casing part at 2640' prevents production of any zones below the Pictured Cliffs. A cement plug was set from above the Mesaverde zone at 4335' to 4540' when the well was completed. The Pictured Cliffs zone was squeezed in September 1960 with 100 sx of regular cement containing 4% gel and 2% CaCl and 50 sx of regular cement containing 2% CaCl (119 sx squeezed into formation and 30 sx left in 5 1/2" casing). The top of the cement in the 5 1/2" casing is at 2400'. We see no further economic possibilities for the well, therefore we propose to plug and permanently abandon the well as per the plugging program below:

1st Plug - Set a cement plug inside 5 1/2" casing from top of existing cement plug at 2400' to 1775' (55' above Ojo Alamo top).

Note: Cement behind casing already covers the Ojo Alamo formation, as evidenced by the attached temperature survey.

2nd Plug - Perforate 5 1/2" casing at 300' and circulate cement in 10 3/4" - 5 1/2" casing annulus to surface.

3rd Plug - Set a cement plug inside 5 1/2" production casing from 30' to surface.

A standard marker will be set at the surface and the location cleaned and restored.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. E. Qab

TITLE Area Superintendent

DATE 10-31-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

TEMPERATURE SURVEY

COMPANY SHELLY OIL COMPANY
WELL JICAPILLA AFACHE C-2 FIELD
COUNTY RIO ARriba STATE NEW MEXICO
SEC. 28 TWP. 25N RGE. 5W

APPROX. TOP CEMENT 1475'

Survey Begins at 1000' Ft. Ends at 2453' Ft.
Approx. Fill-Up OVER 100% Max. Temp. 112° @ 2453'
Log Measured From R.T. Run No. 1

Casing Size	Casing Depth	Diam of Hole	Depth
<u>5½" from 0'</u>	<u>to 4876'</u>	<u>8½" from</u>	<u>to</u>
<u>from</u>	<u>to</u>	<u>from</u>	<u>to</u>

Date of Cementing	<u>MAY 19, 1956</u>	Time	<u>8:00 A.M.</u>
Date of Survey	<u>MAY 19, 1956</u>	Time	<u>3:00 P.M.</u>
Amount of Cement	<u>200 SACKS</u>	Type	<u>REGULAR</u>
Amount of Admix.	<u>4% GEL</u>	Type	
Recorded by	<u>SMITH</u>	Witnessed by	<u>J.W. TURNER</u>

REMARKS OR OTHER DATA

HOWCO DV TOOL SET @ 2888'

TEMPERATURE IN DEGREES FAHRENHEIT



