FOIT (A)	n 9- 8 pri l 19	331 b 52)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Budget Bureau No. 42-R359.4. Approval expires 12-31-60.
Indian Agency Jicarilla
Apache
Allottee Contract No.67
Lease No.

NOTICE OF INTENTION TO DRILL		SUBSEQUENT I	REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE	PLANS		REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WAT	ER SHUT-OFF.	SUBSEQUENT I	REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL	OR REPAIR WELL	SUBSEQUENT I	REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OF	R ACIDIZE.	SUBSEQUENT I	REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR	ALTER CASING	SUPPLEMENTA	RY WELL HISTORY.
NOTICE OF INTENTION TO ABANDON	WELL	K	
(indica	TE ABOVE BY CHECK MARK N	ATURE OF REPORT,	NOTICE, OR OTHER DATA)
	<u>.</u>		June 25
/all No. 1-29 :	noted 900 ft from	[N] ;	990 ft. from E line of se
		in a committee and	The second line of se
W/4 29 (14 Sec. and Sec. No.)	25N (Twp.)	(Range)	NMPM (Meridian)
Basin Dakota	Rio Arri		New Mexico
(Field)		Subdivision)	(State of Territory)
	DETAIL	S OF WORK	3
	DETAIL o objective sands; show sizes, ing points, and all oth	S OF WORK , weights, and leng ler important prop	ths of proposed casings; indicate mudding
b bing and run HOWCO R perf. 6788 to 6940' bing and packer, set marker in to of ho	DETAIL objective sands; show sizes ing points, and all oth TTS squeeze pack w/50 sacks regulates 45 sx. cement p	S OF WORK, weights, and lenguar important properties on 2" to the color of the colo	ths of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
b bubing and run HOWCO R perf. 6788 to 6940' ubing and packer, set marker in tog of ho	DETAIL objective sands; show sizes ing points, and all oth TTS squeeze pack w/50 sacks regulates 45 sx. cement p	S OF WORK, weights, and lenguar important properties on 2" to the color of the colo	ths of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
State names of and expected depths to b ubing and run HOWCO R	DETAIL objective sands; show sizes ing points, and all oth TTS squeeze pack w/50 sacks regulates 45 sx. cement p	S OF WORK, weights, and lenguar important properties on 2" to the color of the colo	ths of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
b bubing and run HOWCO R perf. 6788 to 6940' ubing and packer, set marker in tog of ho	DETAIL objective sands; show sizes ing points, and all oth TTS squeeze pack w/50 sacks regulates 45 sx. cement p	S OF WORK, weights, and lenguar important properties on 2" to the color of the colo	ths of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with work of 52 casing.
b bubing and run HOWCO R perf. 6788 to 6940' ubing and packer, set marker in tog of ho	DETAIL objective sands; show sizes ing points, and all oth TTS squeeze pack w/50 sacks regulates 45 sx. cement p	S OF WORK, weights, and lenguar important properties on 2" to the color of the colo	ths of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with work of 52 casing.
b bing and run HOWCO R perf. 6788 to 6940 bing and packer, set marker in to: of ho	DETAIL objective sands; show sizes ing points, and all oth TTS squeeze pack w/50 sacks regulates 45 sx. cement p	S OF WORK, weights, and lenguar important properties on 2" to the color of the colo	ths of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with work of 52 casing.
buting and run HOWCO Report. 6788 to 6940 bling and packer, set marker in tog of hoapproval from P.T. M.	DETAIL objective sands; show sizes ing points, and all oth TTS aqueeze pack w/50 sacks regulates coment ples. cGrath 6-18-62 b	S OF WORK, weights, and leng ter important properties on 2" talar neat colug in top by telephone	the of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
tate names of and expected depths to build and run HOWCO Reperf. 6788 to 6940 bling and packer, set marker in tog of hoapproval from P.T. M	DETAIL cobjective sands; show sizes, ing points, and all oth the same of the	S OF WORK, weights, and leng ter important properties on 2" talar neat colug in top by telephone	the of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
tate names of and expected depths to be uping and run HOMCO Report. 6788 to 6940 bling and packer, set marker in top of he approval from P.T. M	DETAIL cobjective sands; show sizes, ing points, and all oth the same of the	S OF WORK, weights, and leng ter important properties on 2" talar neat colug in top by telephone	the of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
tate names of and expected depths to be uping and run HOWCO Report. 6788 to 6940 bling and packer, set marker in tog of hoapproval from P.T. M.	DETAIL cobjective sands; show sizes, ing points, and all oth the same of the	S OF WORK, weights, and leng ter important properties on 2" talar neat colug in top by telephone	the of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.
bing and run HOWCO R perf. 6788 to 6940' bing and packer, set marker in top of ho approval from P.T. M	DETAIL objective sands; show sizes, ing points, and all other of the same of	S OF WORK, weights, and leng ter important properties on 2" talar neat colug in top by telephone	the of proposed casings; indicate mudding osed work) ubing set at 6700 feet. ement, Fill hole with we of 52 casing.

U. S. GOVERNMENT PRINTING OFFICE 16-8487b-8