



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 07601  
Unit Lytle Rents

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Report of Perforation</u>
	<u>Report of Sand-freeing</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 28, 1957

Lytle Rents  
Well No. 1 is located 990 ft. from S line and 990 ft. from W line of sec. 19  
1/4 Section 19 (1/4 Sec. and Sec. No.) 5N (Twp.) 3W (Range) N.M.F.M. (Meridian)  
Undesignated (T.O.) (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perforated 5 1/2" casing 3576-96' w/4 Alex cone shots per ft., total of 80 shots.

Fraced 5 1/2" casing perforations, 3576-96', down 5 1/2" casing, w/40,000# sand & 45,440 gals. water. BDF 2100#, Max. pressure 1500#, Min. pressure 1350#. Max. inj. rate 59.3 bbls. per minute, 10,000 gals. flush & 6600 gals. over-flush. Time of treatment 19 minutes. Shut down pressure 200#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLEY OIL COMPANY

Address Box 400  
Farmington, New Mexico

By (Signed) E. W. Cooper

Title District Superintendent