

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool South Blanco Formation Pebbled Cliffs County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 10/8/60  
Company Artes Oil & Gas Company Lease Arteson-Flonilla Well No. 4-A  
Unit II Sec. 24 Twp. 23N Rge. 4W Purchaser \_\_\_\_\_  
Casing 2 7/8 Wt. 6.90 I.D. 2.441 Set at 3474 Perf. 3434 To 3490  
Tubing \_\_\_\_\_ Wt. \_\_\_\_\_ I.D. \_\_\_\_\_ Set at \_\_\_\_\_ Perf. \_\_\_\_\_ To \_\_\_\_\_  
Gas Pay: From 3434 To 3490 L 3434 xG 0.65 (max) GL 2232 Bar. Press. 12  
Producing Thru: Casing X Tubing \_\_\_\_\_ Type Well Single  
Date of Completion: 10/1/60 Packer \_\_\_\_\_ Reservoir Temp. 83  
Single-Bradenhead-G. G. or G.O. Dual

## OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI										
1.		<u>0.790</u>						<u>23</u>	<u>60 (amb)</u>	<u>7 days</u> <u>3 hrs.</u>
2.										
3.										
4.										
5.										

## FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w p_f}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.355</u>		<u>35</u>	<u>1.0000</u>	<u>0.9500</u>	<u>1.004</u>	<u>420</u>
2.							
3.							
4.							
5.							

## PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
F<sub>c</sub> 5.951 (1-e<sup>-s</sup>) 0.190

Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
P<sub>c</sub> 992 P<sub>c</sub><sup>2</sup> 866.504

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> P <sub>c</sub>
1.	<u>35</u>	<u>1.225</u>	<u>2.380</u>	<u>5.664</u>	<u>0.807</u>	<u>2.032</u>	<u>866.598</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 419 MCFPD; n 0.85COMPANY Artes Oil & Gas CompanyADDRESS Box 970, Farmington, New MexicoAGENT and TITLE ORIGINAL SIGNED BY L. M. STEVENS L. M. Stevens, Dist. Eng.

WITNESSED \_\_\_\_\_

COMPANY \_\_\_\_\_

REMARKS \_\_\_\_\_



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

$Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.

$P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia

$P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

$P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

$P_f$  = Meter pressure, psia.

$h_w$  = Differential meter pressure, inches water.

$F_g$  = Gravity correction factor.

$F_t$  = Flowing temperature correction factor.

$F_{pv}$  = Supercompressability factor.

$n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .

STATE OF NEW MEXICO	
OIL CONSERVATION COMMISSION	
AZTEC DISTRICT OFFICE	
NUMBER OF COPIES RECEIVED	
DATE	
SANTA FE	
FILE	
U.S.G.S.	
L.A.D. OFFICE	
TRANSPORTER	
PRODUCTION OFFICE	
OPERATOR	