


A 10x10 grid with an 'X' in the 2nd column and 3rd row.

LOCATE WELL CORRECTLY



U. S. LAND OFFICE Jicarilla Tr.
SERIAL NUMBER Cont. No. 65
LEASE OR PERMIT TO PROSPECT _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

OR
MAY 13 1959
RECEIVED
NEW MEXICO

LOG OF OIL OR GAS WELL

Company El Paso Natural Gas Company Address Box 997, Farmington, New Mexico
 Lessor or Tract Jicarilla Field So. Blanco P.C. State New Mexico
 Well No. 7-C Sec. 22 T. 25N R. 4W Meridian N.M.P.M. County Rio Arriba
 Location 1650 ft. [N.] of S Line and 800 ft. [E.] of W Line of Section 22 Elevation 7006
 (Strike from relative to nearest)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed ORIGINAL SIGNED H.E. McANALLY
Date August 11, 1959 Title Petroleum Engineer

The summary on this page is for the condition of the well at above date.

Commenced drilling 4-29, 1959 Finished drilling 5-3, 1959

OIL OR GAS SANDS OR ZONES
(Denote gas by G)

No. 1, from 3317 to 3416 (G) No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8	24	8 Rd.	J-55	127	Howco				Surface
9-1/2	15.5	8 Rd.	J-55	3425	Baker				Prod. Csg.
1-1/4	2.4	10 Rd.	Grade "A"	3385					Siphon

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8	138	90	Circulated		
5-1/2	3435	87	Single Stage		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set

Adapters—Material Size

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
		See Well History				

TOOLS USED

Rotary tools were used from 0 feet to 3438 feet, and from feet to feet.

Cable tools were used from feet to feet, and from feet to feet.

DATES

-----7-8-----, 19-59 Put to producing -----, 19-----

The production for the first 24 hours was ----- barrels of fluid of which -----% was oil; -----% emulsion; -----% water; and -----% sediment. Gravity, °Bé. -----

If gas well, cu. ft. per 24 hours 1,653,000..... Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. ----- **971** ----- **A.O.F. = 4018 MCF/D**

EMPLOYEES

_____, Driller _____, Driller
_____, Driller _____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	2787	2787	Tan to gry cr-grn ss interbedded w/gry sh.
2787	2980	193	Ojo Alamo ss. White cr-grn s.
2980	3216	236	Kirtland form. Gry sh interbedded w/tight gry fine grn ss.
3216	3317	101	Fruitland form. Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.
3317	3416	99	Pictured Cliffs form. Gry, fine-grn, tight, varicolored soft ss.
3416	3438	22	Lewis formation. Gry to white dense sh w/silty to shaly ss breaks.

