

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 081220-B
Unit Canada Ojitos Unit

			X

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	X	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

RECEIVED
SEP 6 1963
U. S. GEOLOGICAL SURVEY
NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 5, 1963

Well No. A-23 is located 680 ft. from N line and 620 ft. from E line of sec. 23

NE/4 NE/4 Sec. 23 25N 1W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Undesignated Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7152 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mud logs, cementing points, and all other important proposed work)

Dakota test. Estimated total depth 6500'.

Surface Casing: 300' of 13-3/8" OD 48# H-40 cemented to surface.
Intermediate : Approximately 4400' of 7-5/8" OD 26.40# J-55 cemented with 200 sacks.
Liner: 5-1/2" OD 15.5# J-55 from bottom of 7-5/8" to approximately 6500', cemented with 150 sacks.

If commercial production is indicated, the producing section will be sand-oil fractured.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BOLACK-GREER, INC.

Address 158 Petroleum Center Bldg.

Farmington, New Mexico

By [Signature]

Title Vice-President