


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **MM 04470**
Unit **Mexico-Ped "B"**



SUNDRY NOTICES AND REPORTS ON WELLS

DEC 16 1959

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<input checked="" type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 15, 1959

Mexico-Ped "B"

Well No. **1** is located **790** ft. from **S** line and **1450** ft. from **W** line of sec. **10**
Sec. 18 **25N** **14W** **NMPN**
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Ballard - Pictured Cliffs **Rio Arriba County** **New Mexico**
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **7576** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well was drilled to a total depth of 3900' and 5-1/2" OD casing set at 3498'. Perforated casing 3000' to 3890', and fraced Pictured Cliffs formation, which proved to be nonproductive. Squenced perforations 3000-30' and perforated casing 3734' to 3770'. Fraced perforation 3734-70' and tested, which also proved to nonproductive. It is our intention to plug and abandon well as follows:

Squense perforations 3734-70' with 100 sacks of cement.

100' (40 sacks) cement plug where 5-1/2" OD casing is set.

100' cement plug at bottom of surface, 50' in and 50' out of bottom of surface pipe.

25' (10 sacks) cement plug in top of 10-3/4" OD surface pipe.

All spaces between plugs to be filled with heavy mud-laden fluid.

Verbal approval given to do this work by Mr. Frahl on December 4, 1959

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **SKELLY OIL COMPANY**

Address **Box 436**
Farmington, New Mexico

By **(Signed) P. E. Cospe**
Title **District Superintendent**

