

A blank 10x10 grid for graphing, consisting of 10 columns and 10 rows of squares.

...Depth Cleaned Out.....3490'

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3450 feet, and from feet to feet.
Cable tools were used from 3450 feet to 3525 feet, and from feet to feet.

PRODUCTION

Put to Producing Shut in 8-20-52, 19
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity
GAS WELL: The production during the first 24 hours was 520 M.C.F. plus 0 barrels of
liquid Hydrocarbon. Shut in Pressure 890 lbs.
Length of Time Shut in 6 days.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.	T. Devonian	T. Ojo Alamo.	3050
T. Salt.	T. Silurian	T. Kirtland-Fruitland	3110
B. Salt.	T. Montoya	T. Farmington	
T. Yates.	T. Simpson	T. Pictured Cliffs	3420
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn.	T.	T.	
T. Miss.	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	530	530	Gray shale	<div>OIL CONSERVATION COMMISSION AZTEC DISTRICT OFFICE No. Copies Received 5 DISTRIBUTION Operator / Santa Fe / Proration Office State Land Office U. S. G. S. Transporter / File /</div>			
530	1190	660	Broken sand & shale				
1190	1940	750	Shale, soft, greenish				
1940	2150	210	Sandy shale				
2150	2210	60	Shale				
2210	2240	30	Hard gray sand				
2240	2400	160	Dark shale				
2400	2440	40	Gray sand				
2440	2670	230	Soft gray shale				
2670	2830	160	Sand & shale, broken				
2830	2970	140	Gray shale				
2970	3110	140	Broken sand & shale				
3110	3310	200	Gray, soft shale				
3310	3320	10	Soft gray sand				
3320	3420	100	Dark carbonaceous shale, Thin coal seams.				
3420	3440	20	Dark shale				
3440	3450	10	Light gray, fine sand, show of gas				
3450	3475	25	Broken sand & shale				
3475	3495	20	Sand, hard, shaly				
3495	3515	20	Soft sandy shale				
3415	3525	10	Sand, shaly				
	3525		T.D.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

January 16, 1953 (Date)
Company or Operator G. L. McMahon, Inc. Address Box 512, Farmington, New Mexico
Name John C. Egan Position or Title Agent.