GPO 9 18 50 7

eb. 1	951)	•	
	eb. 19	Feb. 1951)	Feb. 1951)

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	New Mexico
Lease No.	04075
Unit	SW/4

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL	SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHEC	CK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	0ctober 28 , 1959
Schultz-Hill  Vell No. 12 is located 1190 ft  SW/4 Section 13 T 25-N  (1/4 Sec. and Sec. No.) (Twp.)	from ${N \choose S}$ line and ${N \choose W}$ line of sec. 13
So. Blanco P. C. Ext. Rio	County or Subdivision)  New Mexico (State or Territory)
The elevation of the derrick floor above	sea level is 7248 ft.
D	DETAILS OF WORK
State names of and expected depths to objective sands; a	SETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- and all other important proposed work)
State names of and expected depths to objective sands; so ing points, so tober 26, 1959. After drilling	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment-
State names of and expected depths to objective sands; so ing points, so tober 26, 1959. After drilling	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  g to 3820° RKB, plugged and abandoned, and plugs as follows:
State names of and expected depths to objective sands; so ing points, so tober 26, 1959. After drilling	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  g to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.  40 sacks - 3560-3430 feet.
State names of and expected depths to objective sands; so ing points, so tober 26, 1959. After drilling	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  g to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.
State names of and expected depths to objective sands; so ing points, so tober 26, 1959. After drilling	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  g to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.  40 sacks - 3560-3430 feet.  10 sacks in top of 8-5/8" casing, which was
State names of and expected depths to objective sands; a ing points, so ing points, so itober 26, 1959. After drillin spotting cemen	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  g to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.  40 sacks - 3560-3430 feet.  10 sacks in top of 8-5/8" casing, which was
State names of and expected depths to objective sands; a ing points, a stober 26, 1959. After drillin spotting cements	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  g to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.  40 sacks - 3560-3430 feet.  10 sacks in top of 8-5/8" casing, which was
State names of and expected depths to objective sands; a ing points, a stober 26, 1959. After drillin spotting cements	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  18 to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.  40 sacks - 3560-3430 feet.  10 sacks in top of 8-5/8" casing, which was left in hole.
State names of and expected depths to objective sands; a fing points, a stocker 26, 1959. After drilling spotting cements of the spotting cements of the same of t	show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementand all other important proposed work)  18 to 3820° RKB, plugged and abandoned, ent plugs as follows:  40 sacks - 3760-3630 feet.  40 sacks - 3560-3430 feet.  10 sacks in top of 8-5/8" casing, which was left in hole.