

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.
Jicarilla Apache Cont. 148

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Contract 148

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND

**SW/4 Section 15,
T-25-N, R-5-W**

12. COUNTY OR PARISH

Elle Arriba

13. STATE

New Mexico

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

DEC 14 1976

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

U. S. GEOLOGICAL SURVEY

DURANGO, COLO.

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1145' FSL & 1650' FWL, Section 15, T-25-N, R-5-W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6831' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject Basin Dakota well was P&A on 12-11-76 as follows:

1. Retainer set at 7170' and 20 sacks of cement with 6% Gal squeezed into perforations at 7220-64' (locked up after 20 sacks). Spotted cement plug of 10 sacks on retainer.
2. Perforated top of Mesaverde at 4680' with 4 shots. Retainer set at 4560' and squeezed 100 sacks of Neat cement into perforations at 4680'. Spotted cement plug of 10 sacks on retainer.
3. Retainer set at 2675' and squeezed 140 sacks of cement with 2% CaCl₂ into hole in casing at 2828'. Spotted cement plug of 12 sacks over retainer.
4. Perforated 530' with 4 shots. Cemented to surface with 200 sacks of cement with 2% CaCl₂. Cement circulated. Left 14 sacks of cement in casing.
5. Spotted 42' cement plug to surface.
6. Cut off wellhead and erected P&A marker.
7. Cleaned up location.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Engineer

DATE

December 13, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.