



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. NM 05942-B
Unit Bolack

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 3, 1962

Well No. 2 is located 1785 ft. from N line and 2120 ft. from E line of sec. 13

NE/4 SW/4 Sec. 13
(1/4 Sec. and Sec. No.)

25N
(Twp.)

1W
(Range)

N.M.P.M.
(Meridian)

Wildcat
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 7098 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

8- 6-62 TD 4900' RKB. Set 155 joints 4904' of 7-5/8" OD 26.40# J-55 casing at 4898' RKB with 100 sacks cement, 2% gel, 12 1/2# Gilsomite per sack, 1# flocele per sack, followed by 300 sacks cement, 1% gel, 12 1/2# Gilsomite per sack, 1# flocele per sack.

8- 7-62 Ran temperature survey. Top of cement 3700'. Set slips, cut off casing.

8- 8-62 Pressured up on casing to 1000#. No pressure decrease in one hour.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BOLACK, ORRER ET AL

Address 158 Petroleum Center Bldg.

Farmington, New Mexico

By [Signature]

Title Engineer