

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

09-000149

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache "F"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Otero Field

11. SEC., T., R., M., OR B.L.K. AND
SURVEY OR AREA

17, T25N, R5W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer "D", Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1650' FSL, 1650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6622' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

Downhole Commingle

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

The New Mexico Oil Conservation Division has granted Amerada Hess an exception to rule 303-A authorizing the downhole commingling of the Pictured Cliffs and Chacra zones by Administrative Order No. DHC-413.

Procedure to Downhole Commingle:

1. Rig up and pull 3/4" siphon string and 2-3/8" tubing.
2. Trip in hole with drilling bailer and knock Baker Model "D" backer, set in 5" liner at 3500', to total depth of well at 3720'.
3. Run 2-3/8" tubing open-ended and set at 3700'.
4. Place well on production as a downhole commingled Pictured Cliffs/Chacra gas well.

P.C. perforations: 2725'-2788'

CH. perforations: 3588'-3705'

18. I hereby certify that the foregoing is true and correct

SIGNED

D. W. Holmes

TITLE

Petroleum Engineer

8-5-83

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

AUG 11 1983

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

BY

FK

NMOC