

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. S.F. 080539
Unit F. Hart

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF <u>Production</u> <u>X</u>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Report of Perforation</u> <u>X</u>
	<u>Report of Sand Fracing</u> <u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 24, 1957

H. F. Hart
Well No. 1 is located 990 ft. from N line and 1650 ft. from W line of sec. 13
Ed/L. Sec. 13 25N 3W H. F. Hart
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 732 ft.


DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run 7" OD casing (121 jts. 3885') set at 3885' with 150 sacks cement, 25 gal.

Perforated 7" casing with 4 Welox Jet shots per ft. as follows: 3791-3820' (29') with 116 shots.

Fraced through casing perforations 3790-3820' with 40,000# sand and 40,320 gals. water. Flushed with 10,794 gals. water. BDP 2200# - Max. TP 1300# - Min. TP 1200#. Inj. rate 65 BPM. Time of treatment 22 min.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Address

By

Title District Superintendent

