

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

09-000149

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache "F"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Otero Field

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17, T25N, R5W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

1. OIL ☐ GAS ☒ OTHER
WELL WELL

2. NAME OF OPERATOR

AMERADA HESS CORPORATION

3. ADDRESS OF OPERATOR

DRAWER "D", Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

990' FNL, 990' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6608' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data.

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) downhole commingle

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

The New Mexico Oil Conservation Division has granted Amerada Hess
an exception to Rule 303-A authorizing the downhole commingling of the
Pictured Cliffs and Chacra zones by Administrative Order No. DHC-412.

Procedure to Downhole Commingling:

1. Rig up and pull 3/4" siphon string and 2-3/8" tubing.
2. Trip in hole with drilling bailer and knock Baker Model "D" packer,
set in 5-1/2" casing at 3483', to total depth of well at 3775'.
3. Run 2-3/8" tubing open-ended and set at 3700'.
4. Place well on production as a downhole commingled Pictured Cliffs/
Chacra gas well.

P.C. perforations: 2721' to 2784'

CH perforations: 3594' to 3716'

18. I hereby certify that the foregoing is true and correct

SIGNED

L. W. Helmes

TITLE Petroleum Engineer

DATE 7-22-83

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

NMOCC

ACCEPTED FOR RECORD

JUL 25 1983

*See Instructions on Reverse Side

FARMINGTON

BY

RB