


1-K.C.L.-ABQ
1-K.C.L.-SFO
1-File

(SUBMIT IN TRIPLICATE)

Land Office **Santa Fe**
Lease No. **SF 080721-A**
Unit _____



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|--|-----------|--|--|
| NOTICE OF INTENTION TO DRILL | | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | XX | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 15, 19 60

PETRO-FEDERAL
Well No. **1** is located **800** ft. from **S** line and **700** ft. from **E** line of sec. **9**
SE/4 Sec. 9 (1/4 Sec. and Sec. No.) **T 25N** (Twp.) **R 1E** (Range) **10W** (Meridian)
Wilcox (Field) **Rio Arriba** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **7125** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

(Confirming telephone conversation Eaton-Shoper, 6-15-60)

T.D. 3164'. 2-5/8" @ 903'. 4-1/2" @ 2300'. Plugged 3164'-2390'. Bridge Plug @ 2206'. Calculated top of cement within 4-1/2" casing at 1873' following squeeze job. Retrievable cementer stuck in 4-1/2" casing at 1700'. Proposed to attempt to go thru cementer and cut 4-1/2" casing below cementer and recover 4-1/2" casing with cementer within. If not successful will cut 4-1/2" casing at free pt. above cementer and recover casing. Will then cement plug stub of 4-1/2" casing and shoe of 2-5/8" casing 875'-925'. Place 10' cement surface plug. Erected marker. Cleaned up and abandoned road and location. Will sow road and location with crested wheat grass.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **KERN COUNTY LAND COMPANY**

Address **226 Petroleum Center Bldg.,**

Farmington, New Mexico

Original Signed By

C. J. Eaton

By

Title **District Engineer**

1111

1111
1111