

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-11424.

5. LEASE DESIGNATION AND SERIAL NO.

Santa Fe 081220-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

BOLACK-GREER, INC.

3. ADDRESS OF OPERATOR

158 Petroleum Center Building, Farmington, New Mexico4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1908' FSL, 523' FWL, Sec. 11, T-25N, R-1W

7. UNIT AGREEMENT NAME

Cañada Ojitos Unit

8. FARM OR LEASE NAME

9. WELL NO.

12-11

10. FIELD AND POOL, OR WILDCAT

Puerto Chiquito11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 11, T-25N, R-1W**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7220' GL

12. COUNTY OR PARISH

13. STATE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

9- 1-64 PBTD 6648'. TD 6687'. Ran 40 joints 1296' of 5-1/2" OD
17# J-55 casing for liner, landed at 6648' RKB, cemented
with 160 sacks regular cement. Top of liner 5348'.

9- 2-64 Temperature survey showed top of cement at 5350'.

9- 3-64 Pressure tested system with 2,000# with 75# pressure drop in
15 minutes. Pressure tested with 1,000# with 25# pressure
drop in 15 minutes. On both tests had surface leak which
apparently accounted for pressure drop.

RECEIVED

OCT 19 1964

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Albert A. Greer

TITLE

Vice-President

DATE

10-16-64

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.