## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Budg App	et B	ureau expir	es 12	-31-	<b>6</b> 0.		
Indiaz								
	gar.	11		T	b	1		
Allot								_
Loase	No.	10	uri	11	<u> </u>	18.	pė	<u>l</u>
Cont	FR		₩ <b>Q.</b>		46	$\mathbb{W}$		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO PULL OR ALTER COMMONICE OF INTENTION TO ABANDON WELL.	SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
(INDICATE ABOVE BY CHECK M	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jicarilla Contrast 146	Farmington, New Hexico-December 20, 19.60
VACAL STATE OF THE	line of sec.
Well No. 10 is located	1190 ft. from S line and 1550 ft. from W line of sec.
,	Page (Meridian)
33/4 3w/4 of Section 9 (14 Sec. and Sec. No.)	(Twp.) (Range)
Rosin Dakota Field	(State or Territory)
	above sea level is 6726 ft. (RDS)
The elevation of the derrick floor	above sea level and money

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 12-1/4" hole on December 18, 1960 and drilled to 506'. Set 6-5/8" casing at 506' with 425 sacks cement with 2 percent calcium chloride. Circulated 60 sacks coment. After waiting on coment, tested 6-5/8" casing with 500 pei for 30 minutes, which held with no indication of prossure drop. Reduced hole to 7-7/8" at 506' and resumed drilling operations.



I understand that this plan of work must receive approval in writing by the Geological Survey before propagations may be commenced. Company Pan American Petroleum Corporation ORIGINAL SIGNED BY Address F. O. Dex 480 R. M. Bauer, Jr. Parmington, New Maxico Area Sagineer Title\_\_\_\_ Attas L. O. Speer, Jr.

U. S. GOVERNMENT PRINTING OFFICE 16-8437b-8