



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079177
Unit W/2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	XXXX	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 1, 1947, 19.....

Schultz-Canyon Largo Unit
Well No. 2-9 is located 1,650 ft. from [N] line and 1,550 ft. from [W] line of sec. 9
NW/4 Section 9 T 25-North R 6-West N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Canyon Largo San Juan County New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6,271 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

West half of Section 9 is dedicated to this well - subject to the NE/4 of the NW/4 (fee land) being committed to the Canyon Largo Unit upon completion of the well.

Propose to spud with "shot hole" rig; then drill with rotary tools to the bottom of the Pictured Cliffs formation, the top of which is expected at about 2,700 feet. Completion with cable tools, perforating and water fracturing, and/or shooting with solidified nitro-glycerin as conditions warrant.

Casing program: 90 feet of 8-5/8" new 8 rd. thd. 24# casing. ~~XXXXXX~~ Circulate cement to surface, using at least 70 sacks cement.

5-1/2" OD J-55 - 14# or better casing - to be set through Pictured Cliffs formation - cemented with 100 sacks regular cement. To be perforated for hydro-fracturing, etc. as necessary.

1" tubing to be set within 20 feet of total depth for production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Frank A. Schultz, Jr.

Address Box 729
Farmington, New Mexico

By [Signature]
C. Pearson Neal, Agent in Farmington
Title _____

