

(SUBMIT IN TRIPLICATE)

Indian Agency JicarillaContract No. 147

Allottee _____

Co. Lease No. 196183

(Orig. Sgd.) J. W. LONG

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	Subsequent report of aquafree	<input checked="" type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

JICARILLA APACHE TRIBE
OF INDIANS "J"

Farmington, New Mexico, May 14, 1956

Well No. 7 is located 990 ft. from N line and 990 ft. from W line of sec. 8N4/4 of N4/4 of Section 8 25N 5W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)South Blanco Pictured Cliffs Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 6727 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

5/11/56: Set 2982', 77 Jts., 5 1/2" casing at 2991' w/175 sacks 10% gel and 100 sacks neat cement. POB at 8:30 A.M., 5/11/56. Cement did not circulate.

5/12/56: Perforated 5 1/2" casing from 2896 to 2920' w/6 bullet shots per foot. NOWCO aquafree treatment through perforations from 2896' to 2920' w/total of 33,000 gals. water including 800 gals. breakdown, 5200 gals flush and overflush and 27000 gals. in treatment and w/40,000# sand. BD pr. 3100# - broke to 1350#. Ave. injection rate 52 bbls./min. at 1600#. Final pr. 1600#. After 5 min, shut in - 750#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Humble Oil & Refining CompanyAddress Box 1268Farmington, New MexicoBy Russell M. Kelly
Agent

Title _____



