

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
**BURLINGTON
RESOURCES** OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4239, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
990' FSL, 1650' FEL, Sec. 2, T-25-N, R-6-W, NMPM, Rio Arriba County

API # (assigned by OCD)
30-039-06148

5. Lease Number

6. State Oil&Gas Lease #
E-291-5

7. Lease Name/Unit Name
Canyon Largo Unit

8. Well No.
101

9. Pool Name or Wildcat
So. Blanco Pict. Cliffs

10. Elevation:

Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other -
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

12-17-98 MIRU. ND WH. NU BOP. TIH to 2470'. SDON.

12-18-98 TIH to 2815'. Establish circ w/25 bbl wtr. Plug #1: pump 15 sx Class "B" neat cmt @ 2500-2815'. TOOH to 2436'. Circ hole clean w/25 bbl wtr. Circ 1 bbl cmt to surface. TOOH. WOC. TIH w/2 7/8" gauge ring, tag TOC @ 2435'. PT csg to 500 psi, failed. Perf 2 sqz holes @ 2415'. TOOH. TIH w/cmt retainer, set @ 2356'. TOOH. Establish injection. Plug #2: pump 123 sx Class "B" neat cmt below cmt retainer outside csg @ 2100-2415'. Pump 20 sx Class "B" neat cmt above cmt retainer inside csg @ 1642-2376'. TOOH to 1800'. Circ hole clean. WOC. SD for weekend.

12-21-98 Load csg w/wtr. Establish circ down csg & out bradenhead. PT csg to 500 psi, failed. TIH, tag TOC @ 1775'. TOOH. TIH, perf 2 sqz holes @ 620'. TOOH. TIH w/cmt retainer, set @ 545'. TOOH. PT csg to 500 psi/5 min, OK. Establish injection. Plug #3: pump 51 sx Class "B" neat cmt below cmt retainer outside csg @ 520-620'. Pump 3 sx Class "E" neat cmt above cmt retainer to 461'. TOOH. TIH, perf 2 sqz holes @ 159'. TOOH. Establish circ down csg & out bradenhead. Plug #4: pump 64 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. SDON.

12-22-98 ND BOP. Cut off WH. Fill 2 7/8" csg, & 2 7/8" x 8 5/8" annulus w/5 sx Class "E" neat cmt. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 12-22-98.

(Henry Villeneuve, OCD on location 12-18-98 & 12-21-98)

SIGNATURE
no

Regulatory Administrator January 11, 1999

(This space for State Use)

Approved by _____ Title _____ Date _____