

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **073885**
Unit **Canyon Largo Unit**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 25, 1959

Well No. **65** is located **1150** ft. from **N** line and **1520** ft. from **E** line of sec. **3**


ME **Sec. 3** **25N** **6W** **N.M.P.M.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
So. Blanco P.C. Ex. **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6733** ft.

DETAILS OF WORK

(State names of any expected or actual productive sands; show sizes, weights, and lengths of proposed casing; indicate casing joints, cementing points, and all other important proposed work.)

On 2-24-59. Total Depth 2465'.
Ran 70 joints 5 1/2", J-55, 15.5#, casing (2463') set at 2463' with 10 sacks
regular cement, 10 sacks Dixie, 6 cu. ft. Stratacrete 46, 24 Gal, followed
with 50 sacks Neat cement.
Held 1000# for 30 minutes.
Top of cement by temperature survey at 2530'.



understanding that the information furnished is for the use of the Geological Survey and is not to be used for any other purpose.

Company **El Paso Natural Gas Company**

Address **Box 977**

Farmington, New Mexico

By **W. E. THURMON**

Petroleum Engineer

Title